

Title (en)

Weft pullback control method

Title (de)

Verfahren zur Steuerung des Schussfadenrückzuges

Title (fr)

Procédé de commande du rappel de fil de trame

Publication

**EP 1310587 A2 20030514 (EN)**

Application

**EP 02013834 A 20020621**

Priority

JP 2001210297 A 20010711

Abstract (en)

A weft pullback control method controls a weft pullback device (4) included in a fluid-jet loom (1) having a weft storage device (2) for storing a length of a weft (5) unwound from a yarn package (6), and a picking nozzle (3), and disposed between the weft storage device (2) and the picking nozzle (3) to pull back a leading end part of the weft (5) extending between the weft storage device (2) and the picking nozzle (3) after the completion of a picking operation. The weft pullback control method makes the weft pullback device (4) pull back the weft (5) by a length greater than that by which the weft (5) is pulled back while the fluid-jet loom (1) is in operation, at least in a particular period in a period between the stoppage of the fluid-jet loom (1) and the start of the first picking operation after the restart of the fluid-jet loom (1). <IMAGE>

IPC 1-7

**D03D 47/34**

IPC 8 full level

**D03D 47/28** (2006.01); **D03D 47/34** (2006.01)

CPC (source: EP)

**D03D 47/34** (2013.01)

Cited by

EP1741817A1; WO2018009119A1

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)

**EP 1310587 A2 20030514**; **EP 1310587 A3 20030917**; CN 1283862 C 20061108; CN 1396324 A 20030212; JP 2003020544 A 20030124; JP 3654350 B2 20050602

DOCDB simple family (application)

**EP 02013834 A 20020621**; CN 02141045 A 20020711; JP 2001210297 A 20010711