

Title (en)

Safety door closure profile

Title (de)

Schliesskantensicherheitsprofil

Title (fr)

Profil de sécurité pour arête de vantail

Publication

EP 1310624 B1 20091007 (DE)

Application

EP 02018942 A 20020826

Priority

DE 10155466 A 20011112

Abstract (en)

[origin: EP1310624A2] A hollow elastomer section has a fastening section (2) and two chamber sections connected to it. One of the chamber sections contains switching elements that trigger a switching pulse fed to an evaluating unit if touched on both sides. The chamber section adjacent to the fastening section forms a switching chamber (3) linked to an outer chamber section forming an after-running chamber (4).

IPC 8 full level

E05F 15/44 (2015.01); **F16P 3/12** (2006.01); **H01H 3/14** (2006.01)

CPC (source: EP)

E05F 15/44 (2015.01); **H01H 3/142** (2013.01)

Cited by

CN110621842A; EP2587509A1; CN103077836A; EP1876048A1; EP2631926A1; WO2018029342A1; US10879017B2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR

DOCDB simple family (publication)

EP 1310624 A2 20030514; **EP 1310624 A3 20070124**; **EP 1310624 B1 20091007**; AT E445076 T1 20091015; DE 10155466 A1 20030522; DE 50213897 D1 20091119; DK 1310624 T3 20100118; ES 2334644 T3 20100315; PT 1310624 E 20091209

DOCDB simple family (application)

EP 02018942 A 20020826; AT 02018942 T 20020826; DE 10155466 A 20011112; DE 50213897 T 20020826; DK 02018942 T 20020826; ES 02018942 T 20020826; PT 02018942 T 20020826