

Title (en)

Dry coating method

Title (de)

Trockenlackier-Verfahren

Title (fr)

Procédé de vernissage à sec

Publication

EP 1314558 A2 20030528 (DE)

Application

EP 01811177 A 20011204

Priority

CH 21762001 A 20011127

Abstract (en)

Dry lacquering process produces transfer-lacquering machines for coating both sides of printed products of different materials. <??>Preferred Features: A machine is used consisting of a support material (2, 2a) coated with lacquer and bonding agent, a pressure roller (3, 3a) for heat-transfer of the thin lacquer layer together with the bonding agent onto a printed product printed on both sides, a peeling device removing a thin lacquer layer, and a roller device for rolling up the empty support material.

Abstract (de)

Mit dem angemeldeten Verfahren wird erstmals die Möglichkeit gegeben, ein Druckerzeugnis beidseitig trocken zu lackieren. <IMAGE>

IPC 1-7

B41F 23/08; B44C 1/10; B44C 1/17

IPC 8 full level

B41F 23/08 (2006.01)

CPC (source: EP)

B41F 23/08 (2013.01)

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)

EP 1314558 A2 20030528; **EP 1314558 A3 20040915**; CH 696463 A5 20070629

DOCDB simple family (application)

EP 01811177 A 20011204; CH 21762001 A 20011127