

Title (en)
TWO CYCLE ENGINE HAVING MINIMAL LUBRICATION

Title (de)
ZWEITAKTMOTOR MIT MINIMALSCHMIERUNG

Title (fr)
MOTEUR A DEUX TEMPS A LUBRIFICATION MINIMALE

Publication
EP 1317606 A1 20030611 (DE)

Application
EP 01974251 A 20010913

Priority
• DE 10045725 A 20000915
• EP 0110602 W 20010913

Abstract (en)
[origin: WO0223016A1] The invention relates to a two cycle engine (1) comprising a lean lubrication system, whereby the lubrication oil is only applied in the area of a contact surface between a piston (3) and a cylinder (2). An oil outlet (12) is provided in or below a running surface (11) pertaining to the cylinder (2) for this purpose. An oil aerosol can be applied alternately, according to the position of the piston (3), onto the running surface of a shaft (9) pertaining to the piston (3) and onto the running surface (11) of the cylinder (2) via said oil outlet.

IPC 1-7
F01M 1/08

IPC 8 full level
F01M 1/06 (2006.01); **F01M 1/08** (2006.01); **F01M 1/16** (2006.01); **F01M 11/00** (2006.01); **F02B 63/02** (2006.01); **F02B 75/16** (2006.01); **F02B 75/02** (2006.01)

CPC (source: EP US)
F01M 1/08 (2013.01 - EP US); **F02B 63/02** (2013.01 - EP US); **F02B 75/16** (2013.01 - EP US); **F01M 2001/083** (2013.01 - EP US); **F02B 2075/025** (2013.01 - EP US)

Citation (search report)
See references of WO 0223016A1

Designated contracting state (EPC)
CH DE LI SE

DOCDB simple family (publication)
WO 0223016 A1 20020321; DE 10045725 A1 20020404; DE 10045725 B4 20050504; DE 50110278 D1 20060803; EP 1317606 A1 20030611; EP 1317606 B1 20060621; JP 2004509261 A 20040325; US 2004011308 A1 20040122; US 6932046 B2 20050823

DOCDB simple family (application)
EP 0110602 W 20010913; DE 10045725 A 20000915; DE 50110278 T 20010913; EP 01974251 A 20010913; JP 2002527638 A 20010913; US 36384503 A 20030306