

Title (en)
ELECTRICAL JUNCTION UNIT

Title (de)
ELEKTRISCHE SCHALTEINHEIT

Title (fr)
BLOC DE JONCTION ELECTRIQUE

Publication
EP 1317784 B1 20071024 (FR)

Application
EP 01969880 A 20010912

Priority
• FR 0102834 W 20010912
• FR 0011609 A 20000912

Abstract (en)
[origin: WO0223675A1] The invention concerns a device comprising two conductive spaced apart components (3, 4) and a blade (5) in the form of a conductive segment mobile between a position closing the circuit wherein it is in contact with the two conductive components and a position opening the circuit, wherein it is spaced apart from said components. The blade is mounted locked in translation on a rod (7) axially mobile in the box between a retracted position in the box wherein the blade (5) is in contact with the conductive components and a projecting position wherein the blade is spaced apart from the conductive components, means being provided to maintain the rod stable in those two positions.

IPC 8 full level
H01H 27/00 (2006.01); **H01R 9/26** (2006.01)

CPC (source: EP KR US)
H01H 27/00 (2013.01 - EP US); **H01R 9/26** (2013.01 - KR); **H01R 9/2633** (2013.01 - EP US)

Designated contracting state (EPC)
BE DE ES GB IT

DOCDB simple family (publication)
WO 0223675 A1 20020321; AU 9001301 A 20020326; CN 100570956 C 20091216; CN 1455974 A 20031112; DE 60131093 D1 20071206; DE 60131093 T2 20080731; EP 1317784 A1 20030611; EP 1317784 B1 20071024; ES 2294029 T3 20080401; FR 2813991 A1 20020315; FR 2813991 B1 20040820; KR 100781293 B1 20071130; KR 20030071758 A 20030906; US 2004011630 A1 20040122; US 6762374 B2 20040713

DOCDB simple family (application)
FR 0102834 W 20010912; AU 9001301 A 20010912; CN 01815480 A 20010912; DE 60131093 T 20010912; EP 01969880 A 20010912; ES 01969880 T 20010912; FR 0011609 A 20000912; KR 20037003616 A 20030312; US 36204703 A 20030602