

Title (en)

Slide fasteners using a copper alloy having excellent continuous castability

Title (de)

Reissverschlüsse aus Kupferlegierung mit ausgezeichneter Stranggiessen-Vergiessbarkeit

Title (fr)

Fermetures à glissière en alliage de cuivre présentant une excellente coulabilité en continu

Publication

EP 1319728 B1 20071219 (EN)

Application

EP 02024279 A 20021031

Priority

JP 2001381142 A 20011214

Abstract (en)

[origin: EP1319728A1] The object of the present invention is to provide a copper alloy for slide fasteners which has excellent whiteness, does not contain nickel and hence does not have the problem of nickel allergy, and has excellent continuous castability and casting quality. The composition of the alloy for slide fasteners is represented by the general formula $Cu_aZn_bMn_c$, wherein regarding a, b and c, in mass%, $10 \leq b \leq 20$, $8 \leq c \leq 15$, and a is a remainder, with unavoidable impurities being contained. Moreover, the structure of the alloy is preferably made to be a single alpha phase at room temperature, and the surface of the alloy is plated.

IPC 8 full level

A44B 19/00 (2006.01); **A44B 19/26** (2006.01); **B22D 11/00** (2006.01); **C22C 9/04** (2006.01); **C22C 9/05** (2006.01)

CPC (source: EP US)

A44B 19/00 (2013.01 - EP US); **C22C 9/04** (2013.01 - EP US); **C22C 9/05** (2013.01 - EP US); **Y10T 24/2598** (2015.01 - EP US)

Cited by

DE102015013201A1; CN107022694A; EP1938705A3; DE102015013201B4; EP3156510A1; US10041149B2

Designated contracting state (EPC)

DE ES FR GB IT

DOCDB simple family (publication)

EP 1319728 A1 20030618; **EP 1319728 B1 20071219**; DE 60224159 D1 20080131; DE 60224159 T2 20081204; ES 2296866 T3 20080501; JP 2003183750 A 20030703; JP 3713233 B2 20051109; US 2003110601 A1 20030619

DOCDB simple family (application)

EP 02024279 A 20021031; DE 60224159 T 20021031; ES 02024279 T 20021031; JP 2001381142 A 20011214; US 28322602 A 20021030