

Title (en)

DEVICE FOR DETECTING THE USE OF A BELT AND THE SERVICE LIFE OF THE RESTRAINT SYSTEMS

Title (de)

VORRICHTUNG ZUM ERFASSEN DER GURTBENUTZUNG UND LEBENSDAUER DER RÜCKHALTESYSTEME

Title (fr)

DISPOSITIF POUR DETECTER L'UTILISATION D'UNE CEINTURE ET DETERMINER LA DUREE DE VIE DES SYSTEMES DE RETENUE

Publication

**EP 1320477 A1 20030625 (DE)**

Application

**EP 01925285 A 20010202**

Priority

- DE 0100611 W 20010202
- DE 10010415 A 20000303

Abstract (en)

[origin: DE10010415C1] The device has belt switches in belt locks to monitor belt lock tongues in plug connection with corresponding locks during travel. The times of use and non-use of safety belts are recorded during travel and for an accident by a program in a microcomputer and/or sensors and/or a controller output at least one signal in the event of an accident to burn out fuses and/or display lamps. The device has fuses (61,61a), display lamps (62,62a), sensors (52,52a), a controller, a visual display screen and/or a microcomputer and current leads supplied with current after switching on current switch (50) connected to the main current lead (70) of a battery (56). Belt switches (9.5,9.5a) in belt locks monitor belt lock tongues in plug connection with corresponding locks during travel. The times of use and non-use of safety belts are recorded during travel and for an accident by a program in the microcomputer and/or the sensors and/or controller output at least one signal in the event of an accident to burn out the fuses and/or display lamps.

[origin: DE10010415C1] The device has belt switches in belt locks to monitor belt lock tongues in plug connection with corresponding locks during travel. The times of use and non-use of safety belts are recorded during travel and for an accident by a program in a microcomputer and/or sensors and/or a controller output at least one signal in the event of an accident to burn out fuses and/or display lamps. The device has fuses (61,61a), display lamps (62,62a), sensors (52,52a), a controller, a visual display screen and/or a microcomputer and current leads supplied with current after switching on current switch (50) connected to the main current lead (70) of a battery (56). Belt switches (9.5,9.5a) in belt locks monitor belt lock tongues in plug connection with corresponding locks during travel. The times of use and non-use of safety belts are recorded during travel and for an accident by a program in the microcomputer and/or the sensors and/or controller output at least one signal in the event of an accident to burn out the fuses and/or display lamps.

IPC 1-7

**B60R 22/48**; B64D 25/06

IPC 8 full level

**B60R 22/48** (2006.01)

CPC (source: EP US)

**B60R 22/48** (2013.01 - EP US); **B60R 2022/4816** (2013.01 - EP US); **B60R 2022/4866** (2013.01 - EP US)

Citation (search report)

See references of WO 0164485A1

Designated contracting state (EPC)

DE ES FR GB SE

DOCDB simple family (publication)

**DE 10010415 C1 20010705**; CA 2399917 A1 20010907; CA 2399917 C 20080902; EP 1320477 A1 20030625; EP 1332933 A2 20030806; EP 1332933 A3 20060823; EP 1332933 B1 20120502; ES 2387266 T3 20120919; US 2004051293 A1 20040318; WO 0164485 A1 20010907; WO 0164485 B1 20011213

DOCDB simple family (application)

**DE 10010415 A 20000303**; CA 2399917 A 20010202; DE 0100611 W 20010202; EP 01925285 A 20010202; EP 03005907 A 20010202; ES 03005907 T 20010202; US 20482703 A 20030109