

Title (en)

METHOD FOR OPERATING A COMMUNICATIONS SYSTEM

Title (de)

VERFAHREN ZUR ANZEIGE VON SYSTEMSPEZIFISCHEN MELDUNGEN AUF ENDGERÄTEN BELIEBIGER HERSTELLER

Title (fr)

PROCEDE PERMETTANT LE FONCTIONNEMENT D'UN SYSTEME DE COMMUNICATION

Publication

EP 1320982 A2 20030625 (DE)

Application

EP 01978095 A 20010907

Priority

- DE 0103457 W 20010907
- DE 10046337 A 20000919

Abstract (en)

[origin: WO0228080A2] The invention relates to a method for operating a communications system comprising at least one communications facility and at least one communications terminal. According to said method, a system-specific message (SYS-MSG) that can be displayed on a user interface device (UI) of the communications terminal (TE1, TE2, TE3, MS) and that is sent from the communications facility (PBX) to the communications terminal (TE1, TE2, TE3, MS) is converted according to a protocol for a wireless text and/or graphics transmission and is displayed on the user interface device (UI). When a user inputs a selection (SI), made on the basis of a system-specific message (SYS-MSG) that is displayed on the user interface device (UI), address information (AI) assigned to the input selection (SI) is transmitted to the communications facility (PBX) and is converted into a system-specific message (SYS-MSG) for activating or deactivating a performance characteristic or a service.

[origin: WO0228080A2] In prior art, communications terminals, which are connected to a communications facility, can only display text or graphic information which has been predetermined and generated by the respective communications facility. There are however between the manufacturers of terminals or communications facilities significant differences in interfaces, protocols, and operating principles for displaying text or graphic information on terminals, which, for example, are connected to a communications facility of another manufacturer. It has therefore previously been a complex process to provide system-specific messages by means of a communications facility for the terminals of any manufacturer. The invention relates to a method for operating a communications system comprising at least one communications facility and at least one communications terminal. According to said method, a system-specific message (SYS-MSG) that can be displayed on a user interface device (UI) of the communications terminal (TE1, TE2, TE3, MS) and that is sent from the communications facility (PBX) to the communications terminal (TE1, TE2, TE3, MS) is converted according to a protocol for a wireless text and/or graphics transmission and is displayed on the user interface device (UI).

IPC 1-7

H04M 3/42

IPC 8 full level

H04M 3/42 (2006.01); **H04M 3/493** (2006.01); **H04M 7/12** (2006.01); **H04W 4/12** (2009.01); **H04W 4/18** (2009.01); **H04W 8/26** (2009.01); **H04W 48/08** (2009.01)

CPC (source: EP US)

H04M 3/42153 (2013.01 - EP US); **H04M 3/42314** (2013.01 - EP US); **H04M 3/4931** (2013.01 - EP US); **H04M 7/12** (2013.01 - EP US); **H04M 2201/38** (2013.01 - EP US); **H04W 4/12** (2013.01 - EP US); **H04W 4/18** (2013.01 - EP US); **H04W 8/26** (2013.01 - EP US); **H04W 48/08** (2013.01 - EP US)

Citation (search report)

See references of WO 0228080A2

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

WO 0228080 A2 20020404; **WO 0228080 A3 20030213**; CN 1496650 A 20040512; EP 1320982 A2 20030625; US 2004014495 A1 20040122

DOCDB simple family (application)

DE 0103457 W 20010907; CN 01815830 A 20010907; EP 01978095 A 20010907; US 38079403 A 20030319