

Title (en)  
FACADE STRUCTURE

Title (de)  
FASSADENKONSTRUKTION

Title (fr)  
STRUCTURE DE FACADE

Publication  
**EP 1322824 B1 20081126 (EN)**

Application  
**EP 01974365 A 20011003**

Priority  
• FI 0100860 W 20011003  
• FI 20002200 A 20001006

Abstract (en)  
[origin: WO0229177A1] The façade structure is intended for balconies (P) in buildings. It comprises the combination of a railing structure (KR) and a glazing (LA). The railing structure (KR) comprises the combination of a support structure (1) and cover plate structure (3) connected to it by mounting pieces (2). The glazing (LA) comprises a lower profile piece (4) and an upper profile piece (5), between which there are vertical glass panes (6). Between the mounting piece (2) of the cover plate structure (3), which is connected to the upper part of the railing structure (KR), and the power profile piece (4) of the glazing (LA), there is placed, substantially in the horizontal direction, a connecting piece (8) which has the length of the facade structure (JR) and which is provided with first (1S) and second (2S) adjusting means. The mounting piece (2) and the lower profile piece (4), in turn, comprise third (3S) and fourth (4S) adjusting means. The first (1S) and the third (3S) adjusting means and, on the other hand, the third (2S) and the fourth (4S) adjusting means together form separate adjusting ranges (ESA, TSA) for connecting said mounting piece (2), connecting piece (8) and lower profile piece (4) to each other.  
[origin: WO0229177A1] The façade structure is intended for balconies (P) in buildings. It comprises the combination of a railing structure (KR) and a glazing (LA). The railing structure (KR) comprises the combination of a support structure (1) and cover plate structure (3) connected to it by mounting pieces (2). The glazing (LA) comprises a lower profile piece (4) and an upper profile piece (5), between which there are vertical glass panes (6). Between the mounting piece (2) of the cover plate structure (3), which is connected to the upper part of the railing structure (KR), and the power profile piece (4) of the glazing (LA), there is placed, substantially in the horizontal direction, a connecting piece (8) which has the length of the facade structure (JR) and which is provided with first (1S) and second (2S) adjusting means. The mounting piece (2) and the lower profile piece (4), in turn, comprise third (3S) and fourth (4S) adjusting means. The first (1S) and the third (3S) adjusting means and, on the other hand, the third (2S) and the fourth (4S) adjusting means together form separate adjusting ranges (ESA, TSA) for connecting said mounting piece (2), connecting piece (8) and lower profile piece (4) to each other.

IPC 8 full level  
**E04F 13/14** (2006.01); **E04B 1/00** (2006.01); **E04B 2/96** (2006.01); **E06B 1/70** (2006.01); **E06B 3/46** (2006.01); **E06B 3/92** (2006.01)

CPC (source: EP)  
**E06B 1/702** (2013.01); **E06B 3/4609** (2013.01); **E06B 3/924** (2013.01); **E05Y 2900/15** (2013.01)

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)  
**WO 0229177 A1 20020411**; AT E415531 T1 20081215; AU 9389701 A 20020415; CN 1227430 C 20051116; CN 1479832 A 20040303; CY 1110310 T1 20150114; DE 60136725 D1 20090108; DK 1322824 T3 20090330; EP 1322824 A1 20030702; EP 1322824 B1 20081126; ES 2317937 T3 20090501; FI 108667 B 20020228; FI 20002200 A0 20001006; NO 20031491 D0 20030402; NO 20031491 L 20030402; NO 318491 B1 20050329; PT 1322824 E 20090305

DOCDB simple family (application)  
**FI 0100860 W 20011003**; AT 01974365 T 20011003; AU 9389701 A 20011003; CN 01820052 A 20011003; CY 091100205 T 20090224; DE 60136725 T 20011003; DK 01974365 T 20011003; EP 01974365 A 20011003; ES 01974365 T 20011003; FI 20002200 A 20001006; NO 20031491 A 20030402; PT 01974365 T 20011003