

Title (en)  
METHOD AND SYSTEM FOR ENABLING CENTRALIZED CONTROL OF WIRELESS LOCAL AREA NETWORKS

Title (de)  
VERFAHREN UND SYSTEM ZUR ZENTRALEN STEUERUNG VON DRAHTLOSEN LOKALEN NETZWERKEN

Title (fr)  
PROCEDE ET SYSTEME ASSURANT LA COMMANDE CENTRALISEE DE RESEAUX LOCAUX SANS FIL

Publication  
**EP 1330894 A2 20030730 (EN)**

Application  
**EP 01987586 A 20011022**

Priority  
• US 0151306 W 20011022  
• US 24197500 P 20001023  
• US 91109201 A 20010723

Abstract (en)  
[origin: WO0241587A2] A wireless local area network (WLAN) includes mobile devices that are allowed to transfer wireless connections between WLAN subnets or channels having different access points. The access points connect to a central controller or roaming server that supports seamless hand-offs of mobile devices from one access point to another access point. The roaming server supports the reassignments of session data parameters from one access point to another (e.g., access point address spoofing) so that the mobile device can use the same parameters for communicating to a new access point. The roaming server also supports the seamless handoff of a mobile device from one access point to another by using a master-slave switch technique across two piconets. The roaming server also facilitates the control of access points by establishing a host controller interface and wireless protocol stack in the roaming server then encapsulates host controller commands in a packet based network protocol used for communication between the roaming server and the access points.  
[origin: WO0241587A2] A wireless local area network (WLAN) (36) includes mobile devices (26) that are allowed to transfer wireless connections between WLAN subnets or channels having different access points (24). The access points connect to a central controller or roaming server (22) that supports seamless hand-offs of mobile devices from one access point to another access point. The roaming server supports the reassignments of session data parameters from one access point to another (e.g., access point address spoofing) so that the mobile device can use the same parameters for communicating to a new access point. The roaming server also supports the seamless handoff of a mobile device from one access point to another by using a master-slave switch technique across two piconets. The roaming server also facilitates the control of access points by establishing a host controller interface and wireless protocol stack in the roaming server then encapsulates host controller commands in a packet based network protocol used for communication between the roaming server and the access points.

IPC 1-7  
**H04L 12/28**; **H04L 12/56**; **H04Q 7/38**

IPC 8 full level  
**H04L 12/28** (2006.01); **H04L 12/56** (2006.01); **H04L 29/06** (2006.01); **H04W 12/08** (2009.01); **H04W 36/00** (2009.01); **H04W 36/08** (2009.01); **H04W 12/00** (2009.01); **H04W 28/18** (2009.01); **H04W 36/18** (2009.01); **H04W 80/06** (2009.01); **H04W 84/00** (2009.01); **H04W 84/12** (2009.01); **H04W 92/10** (2009.01)

CPC (source: EP US)  
**H04L 69/161** (2013.01 - EP); **H04L 69/169** (2013.01 - EP); **H04W 12/033** (2021.01 - EP US); **H04W 36/0011** (2013.01 - EP US); **H04L 69/16** (2013.01 - EP); **H04W 8/26** (2013.01 - EP); **H04W 36/142** (2023.05 - US); **H04W 80/06** (2013.01 - EP); **H04W 84/12** (2013.01 - EP); **H04W 92/10** (2013.01 - EP)

Citation (search report)  
See references of WO 0241587A2

Cited by  
CN102026301A

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)  
**WO 0241587 A2 20020523**; **WO 0241587 A3 20030227**; AU 3978802 A 20020527; CA 2426482 A1 20020523; EP 1330894 A2 20030730; JP 2004514383 A 20040513

DOCDB simple family (application)  
**US 0151306 W 20011022**; AU 3978802 A 20011022; CA 2426482 A 20011022; EP 01987586 A 20011022; JP 2002543871 A 20011022