

Title (en)

Method and apparatus for preventing weft bars in a loom

Title (de)

Verfahren und Vorrichtung zum Vermeiden von Schussstreifen in einer Webmaschine

Title (fr)

Procédé et dispositif pour supprimer des barrures en trame pour un métier à tisser

Publication

EP 1331295 A2 20030730 (EN)

Application

EP 03001137 A 20030120

Priority

JP 2002019831 A 20020129

Abstract (en)

A weft bar prevention technique in a loom which moves a cloth fell position by moving a motor 34, 38 prior to starting operation of the loom is characterized in that correction amount data of the cloth fell position is preset per warp tension, and at the time of preparing to start the loom, the correction amount of the cloth fell position is determined according to the warp tension in a state that the loom is stopped on the basis of the correction amount data, and the cloth fell position is corrected on the basis of the correction amount. <IMAGE>

IPC 1-7

D03D 49/10; D03D 49/04; D03D 51/08

IPC 8 full level

D03D 49/10 (2006.01); **D03D 51/00** (2006.01)

CPC (source: EP)

D03D 49/10 (2013.01); **D03D 51/002** (2013.01)

Cited by

EP1439250A3; EP1460158A3

Designated contracting state (EPC)

BE DE IT

DOCDB simple family (publication)

EP 1331295 A2 20030730; **EP 1331295 A3 20040102**; CN 1446964 A 20031008; JP 2003221759 A 20030808

DOCDB simple family (application)

EP 03001137 A 20030120; CN 03101604 A 20030113; JP 2002019831 A 20020129