

Title (en)
METHOD AND APPARATUS FOR CODING INFORMATION, METHOD AND APPARATUS FOR DECODING CODED INFORMATION, METHOD OF FABRICATING A RECORDING MEDIUM, THE RECORDING MEDIUM AND MODULATED SIGNAL

Title (de)
VERFAHREN UND VORRICHTUNG ZUR INFORMATIONSKODIERUNG, VERFAHREN UND VORRICHTUNG ZUR DEKODIERUNG VON KODierter INFORMATION, VERFAHREN ZUR HERSTELLUNG EINES AUFZEICHNUNGSTRAEGERS, AUFZEICHNUNGSTRAEGER UND MODULiertes SIGNAL

Title (fr)
PROCEDE ET APPAREIL DE CODAGE D'INFORMATION, PROCEDE ET APPAREIL DE DECODAGE D'INFORMATION, PROCEDE DE FABRICATION D'UN SUPPORT D'ENREGISTREMENT, LE SUPPORT D'ENREGISTREMENT ET SIGNAL MODULE

Publication
EP 1332561 A4 20051109 (EN)

Application
EP 00973254 A 20001111

Priority
KR 0001292 W 20001111

Abstract (en)
[origin: WO0241500A1] In the coding device and method, m-bit information words are converted into n-bit code words such that the coding rate m/n is greater than $2/3$. The n-bit code words are divided into a first type and a second type, and into coding states of a first kind and a second kind such that an m-bit information word is converted into an n-bit code word of the first or second kind if the previous m-bit information word was converted into an n-bit code word of the first type and is converted into an n-bit code word of the first kind if the previous m-bit information word was converted into an n-bit code word of the second type. In one embodiment, n-bit code words of the first type end in zero, n-bit code words of the second type end in one, n-bit code words of the first kind start with zero, and n-bit code words of the second kind start with zero or one. Furthermore, in the embodiments, the n-bit code words satisfy a dk-constraint to (1,k) such that a minimum of 1 zero and a maximum of k zeros falls between consecutive ones. The coding device and method are employed to record information on a recording medium and thus create the recording medium. The coding device and method are further employed to transmit information. In the decoding method and apparatus, n-bit code words are decoded into m-bit information words. The decoding involves determining the state of a next n-bit code word, and based on the state determination, the current n-bit code word is converted into an m-bit information word. The decoding device and method are employed to reproduce information from a recording medium, and to receive information transmitted over a medium.

IPC 1-7
G11B 7/24; C08L 53/00; C09D 153/00; C08F 22/40; C08F 290/14

IPC 8 full level
G11B 20/10 (2006.01); **G11B 20/14** (2006.01); **H03M 5/14** (2006.01); **H03M 7/14** (2006.01); **H03M 7/46** (2006.01); **H03M 13/01** (2006.01)

CPC (source: EP)
G11B 20/1426 (2013.01); **H03M 5/145** (2013.01); **H03M 7/46** (2013.01); **H03M 13/01** (2013.01)

Citation (search report)

- [X] US 5696505 A 19971209 - SCHOUHAMER IMMINK KORNELIS A [NL]
- [X] US 6084536 A 20000704 - ARTS PETRUS H M [NL]
- [E] EP 1190488 A1 20020327 - LG ELECTRONICS INC [KR]
- See references of WO 0241500A1

Citation (examination)

- US 4413251 A 19831101 - ADLER ROY L [US], et al
- SHOUHAMER IMMINK K A ET AL: "EXTREMELY EFFICIENT DC-FREE RLL CODES FOR OPTICAL RECORDING", IEEE TRANSACTIONS ON CONSUMER ELECTRONICS, IEEE SERVICE CENTER, NEW YORK, NY, US, vol. 47, no. 4, 1 November 2001 (2001-11-01), pages 910 - 914, XP001200522, ISSN: 0098-3063, DOI: 10.1109/30.982807
- SCHOUHAMER IMMINK K A ET AL: "EFFICIENT DC-FREE RLL CODES FOR OPTICAL RECORDING", IEEE TRANSACTIONS ON COMMUNICATIONS, IEEE SERVICE CENTER, PISCATAWAY, NJ, USA, vol. 51, no. 3, 1 March 2003 (2003-03-01), pages 326 - 331, XP001163611, ISSN: 0090-6778, DOI: 10.1109/TCOMM.2003.809752

Designated contracting state (EPC)
DE FR GB IT NL

DOCDB simple family (publication)
WO 0241500 A1 20020523; AU 1178301 A 20020527; CN 100474782 C 20090401; CN 1423860 A 20030611; EP 1332561 A1 20030806; EP 1332561 A4 20051109; JP 2004514367 A 20040513; JP 4095440 B2 20080604

DOCDB simple family (application)
KR 0001292 W 20001111; AU 1178301 A 20001111; CN 00818304 A 20001111; EP 00973254 A 20001111; JP 2002543791 A 20001111