

Title (en)

Fassade or glazed roof construction and retaining profile

Title (de)

Fassaden- oder Lichtdachkonstruktion und Halteprofil

Title (fr)

Construction de façade ou de toiture vitrée et profilé de fixation

Publication

EP 1338713 B1 20060628 (DE)

Application

EP 03003735 A 20030219

Priority

DE 20202714 U 20020221

Abstract (en)

[origin: EP1338713A2] The faade or light roof construction has a metallic latches and post profiles (1) as well as holder profiles (2) made from plastic. There are screws (1) on the posts, whilst the holder profiles each have at least one, preferably many, hollow chambers (11, 20). The holder profile may be centrally set in a hollow chamber, whilst one of the hollow chambers may have a cross section that is trapezoid or triangular and whose base side is linked to the latch profile. The holder profile may have, on its outer side a groove (12) to receive the screw head (10). There may be bridges (13) that run from the screw head groove to form a sealing (6). Of the three hollow chambers, two of the outer hollow chambers (20) may be built on the side upper edge region of the holder profile, with the third hollow chamber (11) lying between the two hollow chambers.

IPC 8 full level

E04B 2/96 (2006.01); **E04D 3/08** (2006.01)

CPC (source: EP)

E04B 2/967 (2013.01); **E04D 3/08** (2013.01); **E04D 2003/0837** (2013.01); **E04D 2003/0856** (2013.01)

Cited by

DE102015118156A1; EP2116659A3; DE102015118156B4; US8578671B2; WO2015036544A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT SE SI SK TR

DOCDB simple family (publication)

EP 1338713 A2 20030827; **EP 1338713 A3 20040630**; **EP 1338713 B1 20060628**; AT E331854 T1 20060715; DE 20202714 U1 20020502; DE 50304009 D1 20060810; DK 1338713 T3 20070917

DOCDB simple family (application)

EP 03003735 A 20030219; AT 03003735 T 20030219; DE 20202714 U 20020221; DE 50304009 T 20030219; DK 03003735 T 20030219