

Title (en)

Hydraulic pressure relief system for a fuel injection apparatus

Title (de)

Hydraulische Druckentlastungseinrichtung für eine Kraftstoffeinspritzanlage

Title (fr)

Système hydraulique de décharge de pression pour un dispositif d'injection de carburant

Publication

EP 1338787 B1 20061018 (DE)

Application

EP 02026058 A 20021122

Priority

DE 10208576 A 20020221

Abstract (en)

[origin: EP1338787A1] Pressure-discharge device for an injection system of an internal combustion engine is designed as a hydraulically controlled pressure relief valve (33). The pressure on the front side (25) of a low lift pump (21) serves as the control pressure. Preferred Features: The pressure relief valve has a housing (35) with a stepped bore (37) guiding a stepped piston (39). An annular surface of the stepped piston and the stepped bore define an annular chamber (41) which is impinged upon by the pressure on the front side of the low lift pump. The stepped piston is spring-loaded and is pressed with a first end face (43) onto a seal seat (45) against the hydraulic pressure exerted by the annular chamber on the stepped piston. A hydraulic connection between the intake side (3) of a high pressure fuel pump (1) and a fuel return (55) is interrupted by the seal seat.

IPC 8 full level

F02M 37/00 (2006.01); **F02M 37/14** (2006.01); **F02M 37/18** (2006.01); **F02M 47/00** (2006.01); **F02M 55/02** (2006.01)

CPC (source: EP)

F02M 37/0029 (2013.01); **F02M 37/0052** (2013.01); **F02M 37/14** (2013.01); **F02M 37/18** (2013.01); **F02M 63/025** (2013.01)

Cited by

CN109154404A; US2012180765A1; US9316187B2; US8973557B2; WO2007051675A1; WO2008148598A1; WO2008017547A1; WO2009059833A1; WO2017152280A1; US10865718B2

Designated contracting state (EPC)

DE FR IT

DOCDB simple family (publication)

EP 1338787 A1 20030827; **EP 1338787 B1 20061018**; DE 10208576 A1 20030911; DE 50208492 D1 20061130; JP 2003269294 A 20030925

DOCDB simple family (application)

EP 02026058 A 20021122; DE 10208576 A 20020221; DE 50208492 T 20021122; JP 2003042161 A 20030220