

Title (en)

METHOD AND DEVICE FOR THE HYSTERESIS CORRECTION OF MEASURED VALUES FOR SENSORS WITH EXTENSOMETERS

Title (de)

VERFAHREN UND VORRICHTUNG ZUR HYSTERESEKORREKTUR VON MESSWERTEN BEI AUFNEHMERN MIT DEHNUNGSMESSSTREIFEN

Title (fr)

PROCEDE ET DISPOSITIF POUR LA CORRECTION D'HYSTERESIS DE VALEURS MESUREES POUR DES CAPTEURS A EXTENSOMETRES

Publication

EP 1340057 A2 20030903 (DE)

Application

EP 01988853 A 20011024

Priority

- DE 10053667 A 20001028
- EP 0112288 W 20011024

Abstract (en)

[origin: WO0235191A1] The invention relates to a method and a device for the hysteresis correction of the measured values of one or more sensors (1), which have been determined in a deformation body using extensometers. According to the invention, each measured value x affected by hysteresis is corrected for the hysteresis error. To achieve this, a hysteresis model is created from the registered strain characteristic curve and the theory of dipole density of the aligned elementary hysteresis in the interior of the deformation body. Said model is used, together with the measured values x affected by hysteresis and the recorded strain history, to derive a correction value for correcting the hysteresis error.

IPC 1-7

G01G 3/14; **G01L 1/22**

IPC 8 full level

G01G 3/14 (2006.01); **G01L 1/22** (2006.01)

CPC (source: EP US)

G01G 3/1416 (2013.01 - EP US); **G01L 1/2275** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)

WO 0235191 A1 20020502; **WO 0235191 A9 20020919**; AU 1905802 A 20020506; DE 10053667 A1 20020508; EP 1340057 A2 20030903; US 2004059532 A1 20040325; US 6928853 B2 20050816

DOCDB simple family (application)

EP 0112288 W 20011024; AU 1905802 A 20011024; DE 10053667 A 20001028; EP 01988853 A 20011024; US 41529903 A 20030428