

Title (en)
PLANISHING DEVICE AND METHOD

Title (de)
AUSBEULVORRICHTUNG UND -VERFAHREN

Title (fr)
PROCEDE ET DISPOSITIF DE DEBOSSSELAGE

Publication
EP 1341621 B1 20050803 (DE)

Application
EP 00977335 A 20001205

Priority
CH 0000643 W 20001205

Abstract (en)
[origin: WO0245877A1] A planishing device (10) contains a pulling element (11), which is joined to lever arms (151.1, 151.2) in an articulated manner. The lever arms (151.1, 151.2) are, at one end (158.1, 158.2), joined in an articulated manner to a joint member (157) that joins the lever arms (151.1, 151.2). In addition, the lever arms (151.1, 151.2) are supported on support devices (162.1, 162.2) at a position (161) that is located at a distance from said ends (158.1, 158.2). These support devices (162.1, 162.2) are pivotally mounted on a supporting element (16). The supporting element is interactively joined to the bearing elements (12.1, 12.2). The pulling element (11) can introduce a tractive force directly or via a joining element (13) into the area of the dent to be removed.

IPC 1-7
B21D 1/06

IPC 8 full level
B21D 1/06 (2006.01)

CPC (source: EP US)
B21D 1/06 (2013.01 - EP US); **Y10S 72/705** (2013.01 - EP US)

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)
WO 0245877 A1 20020613; AT E301011 T1 20050815; AU 1507101 A 20020618; DE 50010892 D1 20050908; EP 1341621 A1 20030910; EP 1341621 B1 20050803; ES 2246906 T3 20060301; US 2004016282 A1 20040129; US 6874347 B2 20050405

DOCDB simple family (application)
CH 0000643 W 20001205; AT 00977335 T 20001205; AU 1507101 A 20001205; DE 50010892 T 20001205; EP 00977335 A 20001205; ES 00977335 T 20001205; US 25839702 A 20021024