

Title (en)

Apparatus for removing continuous web edge trim by suction

Title (de)

Vorrichtung zum Absaugen eines von einer laufenden Warenbahn abgetrennten Randstreifens

Title (fr)

Dispositif pour aspirer les bords coupé d'un matériau en bande

Publication

EP 1344616 B1 20050209 (DE)

Application

EP 03003887 A 20030221

Priority

DE 10208607 A 20020227

Abstract (en)

[origin: EP1344616A1] Edge strip (2) is trimmed from a continuous fabric (3) by a rotary cutter (6) and removed by a suction duct (10). Hinged, spring-loaded (27) feeler (15) is deflected if there is a region (33) where the strip has not been correctly cut so that it is entrained with the fabric and is being pulled out of the suction duct (10). Feeler (15) is linked to a sensor (25) that provides a warning signal (30, 31) or stops the motion (32) of the fabric (3). Preferred Features: The position of the feeler (15) can be adjusted where it projects over the end of the suction duct (10). The sensor (25) can be an electrical switch, or an inductive or capacitance proximity switch. The suction duct (10) ends in a compressed air jet (12) that produces the suction.

IPC 1-7

B26D 7/18

IPC 8 full level

B26D 7/18 (2006.01); D06H 7/06 (2006.01)

CPC (source: EP)

B26D 7/1863 (2013.01); D06H 7/06 (2013.01)

Cited by

CN106637893A; CN110820297A

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT SE SI SK TR

DOCDB simple family (publication)

EP 1344616 A1 20030917; EP 1344616 B1 20050209; AT E288816 T1 20050215; DE 10208607 C1 20030612; DE 50300294 D1 20050317

DOCDB simple family (application)

EP 03003887 A 20030221; AT 03003887 T 20030221; DE 10208607 A 20020227; DE 50300294 T 20030221