

Title (en)  
Sealing arrangement

Title (de)  
Dichtungseinrichtung

Title (fr)  
Dispositif d'étanchéité

Publication  
**EP 1348806 B1 20060726 (DE)**

Application  
**EP 03002708 A 20030206**

Priority  
DE 10214133 A 20020328

Abstract (en)  
[origin: EP1348806A1] A paper processing machine has a seal (10) with a movable tip (20) maintaining the pressure difference between a component and the inner face (12) of a moving (B) drum (18). The tip (20) has a contact surface (22) translating to a non-contact extension (24) separated from the drum by a gap (26). The seal position is esp. radially adjustable to increase or decrease the size of the gap (26). The gap (26) is adjusted by seal swivel (32) action. The pivot (32) point is fixed. The radius (rE) of the non-contact zone (24) is the same or less than that (R) of the moving inner face (12). The radius of curvature (rD) of the contact surface (22) is greater than or the same as that (r) of the transition zone between the contact surface (22) and the non-contact extension (24). The radius of curvature (r) in the transition zone is greater than that (rE) of the non-contact extension (24). The swivel-axis (32) range is variable. The seal (20) is held in a fixture profile (21) by pressure-variable pneumatic hoses (34, 36) working in opposition.

IPC 8 full level  
**D21F 3/10** (2006.01)

CPC (source: EP)  
**D21F 3/10** (2013.01)

Cited by  
EP1508640A1; EP1496153A1; DE102008041127A1; WO2005052250A1; TWI746152B

Designated contracting state (EPC)  
AT DE FI SE

DOCDB simple family (publication)  
**EP 1348806 A1 20031001; EP 1348806 B1 20060726**; AT E334255 T1 20060815; DE 10214133 A1 20031009; DE 50304321 D1 20060907

DOCDB simple family (application)  
**EP 03002708 A 20030206**; AT 03002708 T 20030206; DE 10214133 A 20020328; DE 50304321 T 20030206