

Title (en)
Printing pad for pad printing

Title (de)
Drucktampon für den Tampondruck

Title (fr)
Tampon d'impression pour l'impression au tampon

Publication
EP 1350620 A1 20031008 (DE)

Application
EP 03405049 A 20030203

Priority
CH 5462002 A 20020402

Abstract (en)
Printing tampon (1) for tampon printing comprises a rubber-elastic tampon body (2) fixed at the rear to a plate (4), a holder (5) removably connecting the plate to a tampon lifting device (24), and a quick-acting closure (6) removably connecting the holder to the plate. Preferred Features: The quick-acting closure is a bearing part (7) containing a locking bar and having at least one recess in which a holding cam engages.

Abstract (de)
Der Drucktampon weist einen gummielastischen Tamponkörper (2, 2') auf, der rückseitig an einer Platte (4, 4') befestigt ist. Mit einem Halter (5) ist die Platte (4, 4') lösbar mit einem Tampon-Hubbalken (24) verbindbar. Der Halter (5) weist einen Schnellverschluss (6, 6') auf, der den Halter (5) lösbar mit der Platte (4, 4') verbindet. Vorzugsweise weist der Schnellverschluss (6, 6') ein Lagerteil (7, 7') auf, in dem ein Riegel (8, 8') gelagert ist. Der Drucktampon ermöglicht einen einfachen und schnellen Wechsel. <IMAGE>

IPC 1-7
B41F 17/00

IPC 8 full level
B41F 17/00 (2006.01)

CPC (source: EP)
B41F 17/001 (2013.01)

Citation (applicant)
EP 0712224 A2 19960515 - HITACHI TELECOMM TECH [JP]

Citation (search report)
• [A] US 5852972 A 19981229 - WOLSTENHOLME MARC W [US]
• [A] US 2810976 A 19571029 - SCOTT ARTHUR L
• [A] PATENT ABSTRACTS OF JAPAN vol. 1996, no. 02 29 February 1996 (1996-02-29)

Cited by
CN102653164A; CN103287082A; WO2007075259A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT SE SI SK TR

DOCDB simple family (publication)
EP 1350620 A1 20031008; CH 695447 A5 20060531

DOCDB simple family (application)
EP 03405049 A 20030203; CH 5462002 A 20020402