

Title (en)

Method for monitoring the weft thread in a loom

Title (de)

Verfahren zum Überwachen des Schussfadens in einer Webmaschine

Title (fr)

Procédé pour surveiller le fil de trame dans un métier à tisser

Publication

EP 1350878 B1 20090121 (DE)

Application

EP 02007476 A 20020402

Priority

EP 02007476 A 20020402

Abstract (en)

[origin: EP1350878A1] A focused light beam (8c) is used for sensing. It is determined whether the weft (1) is at the correct location along the desired path of introduction into the shed, at appropriate positions and instants during the machine cycle. The beam is positioned to be interrupted by the weft, when it is on the right path. The weft is deflected to the side in accordance with the machine cycle, such that it passes through the beam during deflection. The instant at which they intersect, is compared with a desired interval (T1). A fault is deduced, should intersection not occur in interval T1, or if intersection occurs in intervals (T2a) or (T2b) before or after T1. A thread-tensioning deflector (3) moves the weft, in accordance with the machine cycle. The duration of weft intersection is compared with a desired interval, measuring also the deflector motion and arranging the light beam suitably. The loom is a shuttle machine, operated with a similar arrangement. Individual weft measurement times are determined for comparison with measured values.

IPC 8 full level

D03D 51/34 (2006.01)

CPC (source: EP)

D03D 51/34 (2013.01)

Cited by

EP2098624A1

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)

EP 1350878 A1 20031008; EP 1350878 B1 20090121; AT E421604 T1 20090215; DE 50213234 D1 20090312

DOCDB simple family (application)

EP 02007476 A 20020402; AT 02007476 T 20020402; DE 50213234 T 20020402