

Title (en)

Drive unit of self-luminous device with degradation detection function

Title (de)

Steuervorrichtung mit Verschlechterungsfeststellung für eine selbstleuchtende Anzeigevorrichtung

Title (fr)

Système de commande pour panneau d'affichage émissif avec détection des détériorations

Publication

EP 1355289 B1 20080702 (EN)

Application

EP 03008469 A 20030411

Priority

JP 2002111464 A 20020415

Abstract (en)

[origin: EP1355289A2] A drive unit which can prevent the decrease of the luminance of a self-luminous device due to degradation or a change in electric characteristic thereof. The drive unit has a semiconductor device having an electric characteristic almost the same as that of the self-luminous device, and drives the semiconductor device in accordance with the frequency of light emission of the self-luminous device. The device generates a characteristic change detection signal indicating the degree of a change in an electric characteristic of the semiconductor device, and supplies the self-luminous device with a drive signal having a current level or a voltage level based on the characteristic change detection signal.
<IMAGE>

IPC 8 full level

G09G 3/20 (2006.01); **G09G 3/30** (2006.01); **G09G 3/32** (2006.01)

CPC (source: EP US)

G09G 3/3216 (2013.01 - EP US); **G09G 3/3283** (2013.01 - EP US); **G09G 3/20** (2013.01 - EP US); **G09G 2310/0256** (2013.01 - EP US); **G09G 2320/029** (2013.01 - EP US); **G09G 2320/043** (2013.01 - EP US); **G09G 2330/021** (2013.01 - EP US)

Cited by

US8576147B2; US8681140B2; US8111215B2; US8013809B2; US8274456B2; US8134546B2; US8482493B2; US7834355B2; US8421715B2; US7482629B2; EP1932137B1; EP1774500A4

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 1355289 A2 20031022; **EP 1355289 A3 20050608**; **EP 1355289 B1 20080702**; DE 60321852 D1 20080814; US 2004027320 A1 20040212; US 7215307 B2 20070508

DOCDB simple family (application)

EP 03008469 A 20030411; DE 60321852 T 20030411; US 41267703 A 20030414