

Title (en)

Coating apparatus for a conductive wire

Title (de)

Beschichtungsvorrichtung für einen leitfähigen Draht

Title (fr)

Dispositif de revêtement d'un fil conducteur

Publication

EP 1357343 B1 20060802 (FR)

Application

EP 03300007 A 20030423

Priority

FR 0205817 A 20020426

Abstract (en)

[origin: EP1357343A1] The assembly (100) with a varnish applicator (1) to shroud a conductor wire has a kiln (2), with a chamber (4) as a passage for the wire (3) to pass through to be coated with a varnish. A heating system acts on the wire in the chamber, between the entry (5) and the exit (6), to evaporate the varnish solvents and bake the deposited varnish. The chamber atmosphere is low in oxygen, with an air feed (11) through an oxygen monitor (10). The chamber fan (13) and the air feed are spaced apart at the chamber, with the fan located between the solvent evaporation zone (B) and the air feed, to carry evaporated solvents towards the air feed to be consumed by combustion outside the varnish baking zone (A).

IPC 8 full level

F26B 13/00 (2006.01); **H01B 13/00** (2006.01); **F26B 23/02** (2006.01); **H01B 13/16** (2006.01)

CPC (source: EP US)

F26B 13/002 (2013.01 - EP US); **F26B 23/022** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1357343 A1 20031029; EP 1357343 B1 20060802; AT E335180 T1 20060815; CA 2425397 A1 20031026; DE 60307164 D1 20060914; DE 60307164 T2 20070712; ES 2269950 T3 20070401; FR 2839084 A1 20031031; FR 2839084 B1 20040716; JP 2004006329 A 20040108; US 2004058292 A1 20040325; US 6923862 B2 20050802

DOCDB simple family (application)

EP 03300007 A 20030423; AT 03300007 T 20030423; CA 2425397 A 20030416; DE 60307164 T 20030423; ES 03300007 T 20030423; FR 0205817 A 20020426; JP 2003118769 A 20030423; US 41968103 A 20030421