

Title (en)

Overload protection for rotary machine tool

Title (de)

Überlastschutz für drehende Werkzeugmaschine

Title (fr)

Protection contre les surcharges pour machine-outil tournant

Publication

EP 1358969 B1 20080416 (DE)

Application

EP 03405287 A 20030423

Priority

DE 10219755 A 20020502

Abstract (en)

[origin: EP1358969A2] A control circuit (6) receives signals from a contactless sensor (8) near the driven member (7b) of the sawtooth clutch (7) and controls the current to the drive motor (1) and an electromagnetic coil (9) surrounding a magnetic clutch (5). This clutch drives the driving portion (7a) of the sawtooth clutch. The angle (alpha) of the drive surfaces (10) of the clutch is chosen so that the driven member is pushed away (X) from the drive member when a torque (M) is applied to the clutch. The magnetic clutch exerts a force (F) which resists disengagement of the clutch up to a given torque value. The clutch drives a reduction gear (2), a chuck (3) and a boring tool (4).

IPC 8 full level

B25F 5/00 (2006.01)

CPC (source: EP US)

B25F 5/001 (2013.01 - EP US)

Cited by

EP2096330A4; EP2447010A1; CN102528770A; EP2517839A3; EP2777880A3; US9126321B2; US8833484B2; WO2007101686A1; US9452520B2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1358969 A2 20031105; EP 1358969 A3 20060802; EP 1358969 B1 20080416; AT E392296 T1 20080515; DE 10219755 A1 20031113; DE 50309612 D1 20080529; ES 2301777 T3 20080701; US 2003221928 A1 20031204; US 6863165 B2 20050308

DOCDB simple family (application)

EP 03405287 A 20030423; AT 03405287 T 20030423; DE 10219755 A 20020502; DE 50309612 T 20030423; ES 03405287 T 20030423; US 42431603 A 20030428