

Title (en)

Method of improving fracture toughness in aluminium-lithium alloys

Title (de)

Verfahren zur Erhöhung der Bruchzähigkeit in Aluminium-Lithium-Legierungen

Title (fr)

Procédé servant à améliorer la ténacité d'alliages d'aluminium et de lithium

Publication

EP 1359232 B2 20140312 (EN)

Application

EP 03015053 A 19980130

Priority

- EP 98903777 A 19980130
- US 3632997 P 19970131

Abstract (en)

[origin: EP1359232A2] An aluminum-lithium alloy is processed with controlled amounts of copper, lithium, manganese and zirconium to produce a product having improved fracture toughness in the short longitudinal (S-L) direction and acceptable strength in the short transverse (ST) direction.

IPC 8 full level

C22C 21/00 (2006.01); **C22C 21/12** (2006.01); **C22F 1/057** (2006.01)

CPC (source: EP)

C22C 21/12 (2013.01); **C22F 1/057** (2013.01)

Citation (opposition)

Opponent :

"Teal Sheets, Registration Record Series, International Alloy Designations and Chemical Composition Limits for Wrought Aluminum and Wrought Aluminum Alloys.", THE ALUMINIUM ASSOCIATION, April 2004 (2004-04-01), pages 3 - 13

Cited by

FR2925523A1; US10724127B2; WO2018144568A1; WO2009103899A1; US8323426B2

Designated contracting state (EPC)

AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

WO 9833947 A1 19980806; AT E250675 T1 20031015; AT E346963 T1 20061215; DE 69818448 D1 20031030; DE 69818448 T2 20040729; DE 69836569 D1 20070111; DE 69836569 T2 20080103; DE 69836569 T3 20140731; EP 0981653 A1 20000301; EP 0981653 A4 20000517; EP 0981653 B1 20030924; EP 1359232 A2 20031105; EP 1359232 A3 20040102; EP 1359232 B1 20061129; EP 1359232 B2 20140312; EP 1359232 B9 20140910; ES 2278093 T3 20070801; ES 2278093 T5 20140716

DOCDB simple family (application)

US 9801584 W 19980130; AT 03015053 T 19980130; AT 98903777 T 19980130; DE 69818448 T 19980130; DE 69836569 T 19980130; EP 03015053 A 19980130; EP 98903777 A 19980130; ES 03015053 T 19980130