

Title (en)
Explosion resisting building closure

Title (de)
Gebäudeabschluss in sprengwirkungshemmender Ausführung

Title (fr)
Fermeture de bâtiment résistant aux explosions

Publication
EP 1361331 B1 20060913 (DE)

Application
EP 03009494 A 20030428

Priority
DE 10220832 A 20020508

Abstract (en)
[origin: DE10220832C1] Sealing device (10) has a damping element (7) on opposite sides of abutment surfaces which are effective in opposing directions of the force acting on the sealing device. Preferred Features: The abutment surfaces are formed by the flange surface of a U-profile (9) facing each other or the abutment surfaces are formed by sections of an L-profile arranged in the longitudinal direction of the assigned frame element and alternating in opposing directions. The U-profile is connected to a holding latch (H) which is anchored in the building part using fixing elements.

IPC 8 full level
E06B 5/12 (2006.01); **E06B 1/60** (2006.01)

CPC (source: EP US)
E06B 1/6084 (2013.01 - EP US); **E06B 5/12** (2013.01 - EP US); **E06B 1/6015** (2013.01 - EP US)

Cited by
DE102004007164A1; EP4187037A1; EP3626904A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 1361331 A2 20031112; EP 1361331 A3 20040114; EP 1361331 B1 20060913; AT E339585 T1 20061015; DE 10220832 C1 20030814; DE 50305005 D1 20061026; ES 2271416 T3 20070416; US 2003208970 A1 20031113; US 6922957 B2 20050802

DOCDB simple family (application)
EP 03009494 A 20030428; AT 03009494 T 20030428; DE 10220832 A 20020508; DE 50305005 T 20030428; ES 03009494 T 20030428; US 43480603 A 20030508