

Title (en)

Method for restarting the printing after an interruption

Title (de)

Verfahren zum Anfahren des Fortdrucks nach einer Druckunterbrechung

Title (fr)

Procédé pour recommencer l'impression après une interruption

Publication

EP 1369234 B1 20070307 (DE)

Application

EP 03010329 A 20030508

Priority

DE 10225244 A 20020607

Abstract (en)

[origin: EP1369234A1] Process for starting a production run comprises feeding ink to the plate cylinder of a printing machine during the printing process, transferring the ink stored in an ink box via an ink siphon to an inker unit assigned to the plate cylinder and consisting of rollers, and feeding moistening water to the plate cylinder during printing via a damping system. During a break in printing, the ink siphon is taken out of action, the ink supply from the inking unit to the plate cylinder is stopped, and the ink siphon is reconnected after the printing break. Preferred Features: The number of ink siphon cycles required before the start of the curve is determined depending on the length of the printing break.

IPC 8 full level

B41F 33/10 (2006.01)

CPC (source: EP)

B41F 33/10 (2013.01); **B41P 2233/11** (2013.01)

Cited by

DE102017200261A1; DE102017200261B4

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

EP 1369234 A1 20031210; EP 1369234 B1 20070307; DE 10225244 A1 20031218; DE 10225244 B4 20160204; DE 50306720 D1 20070419

DOCDB simple family (application)

EP 03010329 A 20030508; DE 10225244 A 20020607; DE 50306720 T 20030508