

Title (en)

REPLACEABLE PRISM FOR APPLANATION TONOMETER

Title (de)

AUSWECHSELBARES PRISMA FÜR EIN APLANATIONSTONOMETER

Title (fr)

PRISME AMOVIBLE POUR TONOMETRE PAR APLANATION

Publication

EP 1377203 A2 20040107 (EN)

Application

EP 02721411 A 20020314

Priority

- US 0207736 W 20020314
- US 81170901 A 20010319

Abstract (en)

[origin: WO02075368A2] A tonometer prism, preferably for a single use, has an applanation surface, an input port arranged to transmit incoming light into the prism, and an output port arranged to transmit outgoing light from the prism. Light entering the input port is directed in an unreflected straight path through the prism to an internal face of the applanation surface. Light internally reflected from the applanation surface proceeds in an unreflected straight path through the prism to the output port.

[origin: WO02075368A2] A tonometer (70, 80, 90), preferably for a single use, has an applanation surface (12), an input port (15) arranged to transmit incoming light into the prism, and an output port (16) arranged to transmit outgoing light from the prism. Light entering the input port is directed in an unreflected straight path through the prism to an internal face of the applanation surface. Light internally reflected from the applanation surface proceeds in an unreflected straight path through the prism to the output port.

IPC 1-7

A61B 3/16

IPC 8 full level

A61B 3/16 (2006.01); **G02B 5/04** (2006.01)

CPC (source: EP)

A61B 3/16 (2013.01); **G02B 5/04** (2013.01)

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)

WO 02075368 A2 20020926; WO 02075368 A3 20021219; AU 2002252345 B2 20050714; CA 2441513 A1 20020926; CA 2441513 C 20110517;
EP 1377203 A2 20040107; EP 1377203 A4 20071114

DOCDB simple family (application)

US 0207736 W 20020314; AU 2002252345 A 20020314; CA 2441513 A 20020314; EP 02721411 A 20020314