

Title (en)  
METHOD FOR SECURING A MOUNTING BAR AT ONE END OF A PRINTING BLANKET AND RESULTING PRINTING BLANKET

Title (de)  
VERFAHREN ZUM ANBRINGEN EINES BEFESTIGUNGSSTABS AN EINEM ENDE EINES DRUCKTUCHS UND SICH ERGEBENDES DRUCKTUCH

Title (fr)  
PROC D DE FIXATION D'UNE BARRETTE UNE EXTR MIT D'UN BLANCHET D'IMPRESSION ET BLANCHET D'IMPRESSION AINSI OBTENU

Publication  
**EP 1377458 A1 20040107 (FR)**

Application  
**EP 02732812 A 20020411**

Priority  

- FR 0201273 W 20020411
- FR 0105044 A 20010412

Abstract (en)  
[origin: FR2823468A1] The method of fixing a bar to a printing blanket cylinder involves cutting back the end (3) of the blanket on which the bar is to be fixed, as far as the main layer (1). A beam (8) is thus disengaged and at least part is glued for fixing of the bar on at least part of the beam on the end of the blanket. Both faces of the beam can be exposed and the bar can be fixed by glue to these faces. Claims include a blanket cylinder made using the method

IPC 1-7  
**B41F 30/04**; **B41N 10/06**; **B41F 27/12**

IPC 8 full level  
**B41F 27/12** (2006.01); **B41F 30/04** (2006.01); **B41N 10/02** (2006.01); **B41N 10/06** (2006.01)

CPC (source: EP US)  
**B41F 27/1281** (2013.01 - EP US); **B41F 30/04** (2013.01 - EP US); **B41N 10/06** (2013.01 - EP US)

Citation (search report)  
See references of WO 02083421A1

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)  
**FR 2823468 A1 20021018**; **FR 2823468 B1 20031031**; DE 60223792 D1 20080110; DE 60223792 T2 20081030; EP 1377458 A1 20040107; EP 1377458 B1 20071128; ES 2296930 T3 20080501; JP 2004523402 A 20040805; JP 4161190 B2 20081008; US 2004159256 A1 20040819; US 6959644 B2 20051101; WO 02083421 A1 20021024

DOCDB simple family (application)  
**FR 0105044 A 20010412**; DE 60223792 T 20020411; EP 02732812 A 20020411; ES 02732812 T 20020411; FR 0201273 W 20020411; JP 2002581199 A 20020411; US 47425804 A 20040316