

Title (en)

Assembly opening portion closing structure in engine

Title (de)

Geometrie zum Schliessen einer Montageöffnung in einem Motor

Title (fr)

Dispositif pour fermer une ouverture de montage dans un moteur

Publication

EP 1378635 B1 20091007 (EN)

Application

EP 03013835 A 20030618

Priority

JP 2002194408 A 20020703

Abstract (en)

[origin: EP1378635A2] In an engine in which a cam shaft can be assembled from the side of one side wall of a cylinder head. First and second assembly opening portions (87 and 98) corresponding respectively to the cam shaft (68) and the rocker shaft (69) are mutually independently provided in one side wall of the cylinder head (41), one of first and second cover members (88 and 99) for individually closing the first and second assembly opening portions (87 and 98) is fitted in one of the first and second assembly opening portions (87 and 98) so as to be inhibited from moving inwards in the axial direction, and the other of the first and second cover members (88 and 99) is fixed to the cylinder head (41) while being engaged with the outside surface of the one of the first and second cover members (88 and 99).

IPC 8 full level

B62M 7/02 (2006.01); **F01L 1/053** (2006.01); **F01L 1/18** (2006.01); **F02B 61/02** (2006.01); **F02F 1/24** (2006.01)

CPC (source: EP)

F01L 1/022 (2013.01); **F01L 1/053** (2013.01); **F01L 1/181** (2013.01); **F02B 61/02** (2013.01); **B62K 2202/00** (2013.01); **F01L 2303/00** (2020.05)

Cited by

EP1895112A4; WO2010043242A1

Designated contracting state (EPC)

ES FR IT

DOCDB simple family (publication)

EP 1378635 A2 20040107; **EP 1378635 A3 20081217**; **EP 1378635 B1 20091007**; CN 1283907 C 20061108; CN 1480631 A 20040310; ES 2332586 T3 20100209; JP 2004036478 A 20040205; JP 3966778 B2 20070829; TW 200402507 A 20040216; TW I225907 B 20050101

DOCDB simple family (application)

EP 03013835 A 20030618; CN 03145487 A 20030701; ES 03013835 T 20030618; JP 2002194408 A 20020703; TW 92116177 A 20030613