

Title (en)
Connecting section

Title (de)
Laibungsanschlussprofil

Title (fr)
Profilé de raccord

Publication
EP 1382772 B1 20080903 (DE)

Application
EP 03450175 A 20030717

Priority
• AT 4862002 U 20020718
• AT 8572002 U 20021219

Abstract (en)
[origin: EP1382772A2] The wedge shaped part of the sealing leg (2) slides in between door or window frame jamb (10) and adjoining insulation layer (14), the leg (2) being undercut (3) on the part furthest from the door frame (10). On the side facing the frame (10) the leg (2) has a co-extruded sealing element (7) set in a leg (1) recess. The sealing element deforms elastically so that it terminates flush with the plaster face (5) when the profile is installed. The element (7) is hollow or solid or again in dome section so that when installed the head part of the dome anchors via an elastic base part into recesses in the sealing leg (2).

IPC 8 full level
E04F 13/06 (2006.01); **E04G 21/30** (2006.01); **E06B 1/62** (2006.01)

CPC (source: EP)
E04F 13/06 (2013.01); **E04F 13/068** (2013.01); **E06B 1/62** (2013.01); **E04F 2013/063** (2013.01); **E06B 2001/624** (2013.01)

Cited by
EP1953329A3; AT15405U1; EP2014859A3; AT519110A4; AT519110B1; WO2009089247A3; WO2009000437A1; US8733721B2; US8752800B2

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 1382772 A2 20040121; **EP 1382772 A3 20041215**; **EP 1382772 B1 20080903**; AT E407272 T1 20080915; DE 50310426 D1 20081016; SI 1382772 T1 20090228

DOCDB simple family (application)
EP 03450175 A 20030717; AT 03450175 T 20030717; DE 50310426 T 20030717; SI 200331453 T 20030717