

Title (en)  
Spark plug

Title (de)  
Zündkerze

Title (fr)  
Bougie d'allumage

Publication  
**EP 1383214 B1 20110824 (EN)**

Application  
**EP 03254453 A 20030715**

Priority  
JP 2002206692 A 20020716

Abstract (en)  
[origin: EP1383214A2] A front end portion of a center electrode 3 is a circular cylindrical center-electrode noble-metal ablation resistance portion 31 whose radius  $r$  mm and length  $l$  mm are determined in such a manner as to satisfy  $5 \leq l/r \leq 20$ . An ignition-performance-improving ground electrode 4 is configured such that a distal end portion thereof is bent in a direction toward the center electrode 3; and a rear end-edge 32t of a distal end surface 4s, 32s is located frontward in relation to a front end surface 31a of the center-electrode noble-metal ablation resistance portion 31. In orthogonal projection on a projection plane P perpendicularly intersecting an axis O of the center electrode 3, the rear end-edge 32t is located outward in relation to the front end surface 31a of the center-electrode noble-metal ablation resistance portion 31. A portion of the ignition-performance-improving ground electrode 4 which includes at least the rear end-edge 32t is a ground-electrode noble-metal ablation resistance portion 32.

IPC 8 full level  
**H01T 13/20** (2006.01); **H01T 13/32** (2006.01); **H01T 13/34** (2006.01); **H01T 13/39** (2006.01)

CPC (source: EP US)  
**H01T 13/32** (2013.01 - EP US); **H01T 13/39** (2013.01 - EP US)

Cited by  
US6798124B2; DE102004021876B3; CN102160247A

Designated contracting state (EPC)  
DE FR GB

DOCDB simple family (publication)  
**EP 1383214 A2 20040121**; **EP 1383214 A3 20090902**; **EP 1383214 B1 20110824**; JP 2004055142 A 20040219; JP 4125060 B2 20080723; US 2004012318 A1 20040122; US 6864623 B2 20050308

DOCDB simple family (application)  
**EP 03254453 A 20030715**; JP 2002206692 A 20020716; US 61959503 A 20030716