

Title (en)

HIGH PRESSURE SEALING ELEMENT FOR INJECTORS

Title (de)

HOCHDRUCKDICHELEMENT FÜR INJEKTOREN

Title (fr)

ELEMENT D'ETANCHEITE HAUTE PRESSION POUR INJECTEURS

Publication

EP 1395748 B1 20050518 (DE)

Application

EP 02735073 A 20020521

Priority

- DE 0201841 W 20020521
- DE 10124602 A 20010521
- DE 10220457 A 20020507

Abstract (en)

[origin: WO02095217A1] The invention relates to an injector for the injection of fuel into the combustion chamber of an internal combustion engine. The injector (1) comprises an injector housing (2) in which a pressure chamber (3) enclosing an insert (7) is embodied. The above may be filled with high pressure fuel by means of a high pressure inlet (21). A control chamber (25) is pressurised by means of the pressure chamber (3), defined by the insert (7), fixed in a drilling (6, 46) in the injector housing (2) and a valve component (26). The valve component (26) may be displaced by executing a stroke displacement (47) within the insert (7). A one-piece metallic sealing element (9) is arranged with a friction fit (14) around the periphery (8) of the insert (7). The sealing element (9) is pressurised with the high pressure in the pressure chamber (3).

IPC 1-7

F02M 61/16; F02M 47/02

IPC 8 full level

F02M 47/00 (2006.01); **F02M 47/02** (2006.01); **F02M 61/16** (2006.01)

CPC (source: EP US)

F02M 47/027 (2013.01 - EP US); **F02M 61/16** (2013.01 - EP US); **F02M 2200/16** (2013.01 - EP US); **F02M 2547/003** (2013.01 - EP US)

Cited by

EP1710429A1; WO2006131411A1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

WO 02095217 A1 20021128; EP 1395748 A1 20040310; EP 1395748 B1 20050518; JP 2004519620 A 20040702; JP 4181419 B2 20081112; US 2004021011 A1 20040205; US 6845756 B2 20050125

DOCDB simple family (application)

DE 0201841 W 20020521; EP 02735073 A 20020521; JP 2002591658 A 20020521; US 33335703 A 20030808