

Title (en)

Return pulley drive for a monocable ropeway with fixed clamps

Title (de)

Antriebsvorrichtung für die Umlenkscheibe einer Einseilumlaufbahn mit festen Klemmen

Title (fr)

Dispositif d'entraînement d'une poulie de renvoi d'un télésiège mono câble à pinces fixes

Publication

EP 1396408 B1 20090325 (FR)

Application

EP 03354068 A 20030723

Priority

FR 0210924 A 20020904

Abstract (en)

[origin: EP1396408A1] The chair lift with an overhead cable (10) for carrying and pulling the chairs comprises a station (14) with a return pulley (12) for the cable and means for positioning the pulley with vertical axis on a cart (30) mounted on a support device (22) for utilizing the pulley driven by a motor-reduction mechanism (20) as the traction pulley. The motor-reduction mechanism (20) comprises an electromotor (34) and a mechanical reductor (36) in the form of two modules of coaxial elements perpendicular to the pulley in substantially vertical direction and positioned on two sides of the pulley. The mechanical reductor (36) is in the form of two independent modules placed on lower and upper sides of the return pulley (12). The high-velocity output element (40) of the electromotor (34) traverses a sheath (38) joined to the cart (30) and is surrounded by the low-velocity output element (44) of the reductor (36). The pulley (12) can rotate around the sheath (38) with interposed bearings and comprises a driving muff connected to the low-velocity output element of the reductor. The mechanical reductor (36) is with reducing gears positioned above the pulley, or the motor-reduction mechanism (20) comprises a motor equipped with an electronic velocity switch for a direct drive of the pulley. The pulley (12) is equipped with a co-wheel (62) cooperating with a spare or emergency motor (64) joined to the cart (30). The support device comprises a base (24) supporting fixed horizontal profiles (28) along which the cart (30) can be displaced by the intermediary of bearings (32). The cart (30) is associated with an elastic strap device (66) for maintaining the cable under tension. The spare motor (64) is an electromotor-reductor driven by a generator.

IPC 8 full level

B61B 12/10 (2006.01); **B61B 11/00** (2006.01); **B61B 12/00** (2006.01)

CPC (source: EP US)

B61B 12/007 (2013.01 - EP US); **B61B 12/10** (2013.01 - EP US)

Cited by

FR2958988A1; US8631745B2; WO2011128532A1; EP1965096B1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1396408 A1 20040310; **EP 1396408 B1 20090325**; AT E426534 T1 20090415; CA 2436761 A1 20040304; DE 60326796 D1 20090507; ES 2323633 T3 20090722; FR 2843928 A1 20040305; FR 2843928 B1 20041210; JP 2004099027 A 20040402; US 2005051049 A1 20050310; US 7036435 B2 20060502

DOCDB simple family (application)

EP 03354068 A 20030723; AT 03354068 T 20030723; CA 2436761 A 20030807; DE 60326796 T 20030723; ES 03354068 T 20030723; FR 0210924 A 20020904; JP 2003308854 A 20030901; US 62839903 A 20030729