

Title (en)
Decoupling device under tensile force

Title (de)
Vorrichtung zum Loskoppeln unter Zugkraft

Title (fr)
Dispositif découpleur en traction

Publication
EP 1403468 B1 20050720 (FR)

Application
EP 03103540 A 20030924

Priority
FR 0211894 A 20020926

Abstract (en)
[origin: EP1403468A1] The decoupling device connecting two parts (14,15) of a structure comprises first parallel fusible rupture parts and second parallel structural rupture parts (72). The rupture parts are planned to rupture when the load applied to the decoupling device attains or exceeds a predetermined load value. The structural rupture parts are planned to resist fatigue whilst the applied load does not reach the predetermined load value.

IPC 1-7
F01D 21/04; **F16B 31/02**

IPC 8 full level
F16B 1/00 (2006.01); **F01D 21/04** (2006.01); **F01D 25/16** (2006.01); **F16B 31/02** (2006.01); **F16P 5/00** (2006.01)

CPC (source: EP US)
F01D 21/045 (2013.01 - EP US); **F01D 25/16** (2013.01 - EP US); **F16B 31/021** (2013.01 - EP US); **F16P 5/005** (2013.01 - EP US);
F16B 2200/63 (2023.08 - EP US)

Cited by
CN113123881A; EP2071141A1; FR2925123A1; FR2976623A1; US11168582B2; US9512847B2; WO2012175864A1

Designated contracting state (EPC)
BE DE FR GB

DOCDB simple family (publication)
EP 1403468 A1 20040331; **EP 1403468 B1 20050720**; CA 2442374 A1 20040326; CA 2442374 C 20110726; DE 60301041 D1 20050825; DE 60301041 T2 20060524; FR 2845126 A1 20040402; FR 2845126 B1 20041203; RU 2003128825 A 20050327; RU 2328627 C2 20080710; US 2004063504 A1 20040401; US 2007081852 A1 20070412; US 7318685 B2 20080115; US 7452152 B2 20081118

DOCDB simple family (application)
EP 03103540 A 20030924; CA 2442374 A 20030924; DE 60301041 T 20030924; FR 0211894 A 20020926; RU 2003128825 A 20030925; US 60859606 A 20061208; US 66251003 A 20030916