

Title (en)
Assembly of an installation for drying moisture loaded material

Title (de)
Baugruppe einer Anlage zum Trocknen von feuchtigkeitsbelastetem Gut

Title (fr)
Assemblage d'une installation pour sécher un matériau chargé d'humidité

Publication
EP 1406056 A1 20040407 (DE)

Application
EP 02405858 A 20021004

Priority
EP 02405858 A 20021004

Abstract (en)
The device has an autoclave that can be heated and evacuated and an evaporator in the autoclave. The goods are heated by the condensation heat of the vapor of a thermal carrier evaporated in the evaporator to extract water from the goods. The evaporator includes a predominantly vertical autoclave wall section heated by the autoclave heating with an arrangement for ensuring heat carrying liquid passes to the wall section as a film. The device has a container (autoclave) (2) for accommodating the drying goods and that can be heated and evacuated with autoclave heating (3) and an evaporator (4) in the autoclave. The goods are heated by the condensation heat of the vapor of a thermal carrier medium evaporated in the evaporator to extract the water in the drying goods. The evaporator includes a predominantly vertical section (18) of an autoclave wall (14) heated by the autoclave heating with an arrangement for ensuring that the heat carrying liquid passes to the wall section as a film. AN Independent claim is also included for the following: (a) system for drying goods containing moisture.

Abstract (de)
Die Baugruppe ist zum Einbau in eine Anlage zum Trocknen von feuchtigkeitsbelastetem Gut unter Vakuum vorgesehen. Sie weist einen der Aufnahme des Trocknungsgutes dienenden heiz- und evakuierbaren Autoklaven (2) auf sowie eine Autoklavenheizung (3) und einen im Autoklaven (2) angeordneten Verdampfer (4). Bei Betrieb der Anlage wird in dieser Baugruppe das Trocknungsgut durch die Kondensationswärme des Dampfes eines im Verdampfer (4) verflüchtigten flüssigen Wärmeträgers aufgeheizt und hierbei dem Trocknungsgut Wasser entzogen. Der Verdampfer (4) enthält einen von der Autoklavenheizung (3) heizbaren, vorwiegend vertikal ausgerichteten Abschnitt (18) einer Wand (14) des Autoklaven (2). Am Wandabschnitt (18) sind Mittel vorgesehen, die eine Führung der Wärmeträgerflüssigkeit in Form eines Films auf dem Wandabschnitt (18) sicherstellen. Diese Baugruppe ist äusserst kostengünstig und zeichnet sich dennoch bei geringem Energieverbrauch und hohem Wirkungsgrad durch ein grosses Nutzvolumen des Autoklaven und durch einfachen Aufbau aus. Zudem wird die Wärmeträgerflüssigkeit über die grossen Wandflächen des Autoklaven (2) geführt und kann so äusserst wirksam, d. h. bei kleiner Differenz zwischen Temperatur des Wandabschnitts und Temperatur der Wärmeträgerflüssigkeit, in Form eines dünnen Films verdampfen. <IMAGE>

IPC 1-7

F26B 21/14; F26B 5/04

IPC 8 full level

F26B 5/04 (2006.01); **F26B 21/14** (2006.01)

CPC (source: EP)

F26B 5/04 (2013.01); **F26B 21/145** (2013.01)

Citation (search report)

- [A] DE 3014831 A1 19810917 - MICAFIL AG [CH]
- [A] DE 19637313 A1 19970327 - HEDRICH VAKUUMANLAGEN WILHELM [DE]
- [A] DE 2756298 A1 19790419 - MICAFIL AG
- [A] EP 0290098 A1 19881109 - MICAFIL AG [CH]
- [A] EP 0752567 A1 19970108 - MICAFIL VAKUUMTECHNIK AG [CH]
- [DA] GMEINER P K: "Modern vapour drying processes and plants", ANNOUNCEMENT MICAFIL VAKUUMTECHNIK, XX, XX, February 1992 (1992-02-01), XP002016470

Cited by

CN108335807A; EP2719984A1; CN113205925A; CN113532029A; WO2014056818A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR

DOCDB simple family (publication)

EP 1406056 A1 20040407; DE 10340920 A1 20040609

DOCDB simple family (application)

EP 02405858 A 20021004; DE 10340920 A 20030905