

Title (en)  
Coupling mechanism for a chronographe

Title (de)  
Kupplungsmechanismus für Chronographen

Title (fr)  
Mécanisme d'embrayage de chronographe

Publication  
**EP 1406132 B1 20060426 (FR)**

Application  
**EP 02079166 A 20021004**

Priority  
• EP 02079166 A 20021004  
• CH 16622002 A 20021004

Abstract (en)  
[origin: EP1406132A1] A spring loaded (9) control lever (10) is actuated by an internal toothed surface (2) and is in contact with a short arm of an L shaped clutch spring (20). The long arm of the spring is shaped as a fork (22) which separates a clutch wheel (17) and seconds wheel (19) normally in friction contact under spring pressure. Tenons (32a,32b) and an eccentric screw (38) allow adjustment of the distance between the short arm and the control lever

IPC 8 full level  
**G04B 19/02** (2006.01); **G04F 7/08** (2006.01)

CPC (source: EP KR US)  
**G04B 19/02** (2013.01 - KR); **G04F 7/08** (2013.01 - EP US); **G04F 7/0828** (2013.01 - EP US)

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR

DOCDB simple family (publication)  
**US 2004066711 A1 20040408; US 7021818 B2 20060404**; AT E324621 T1 20060515; CN 100527021 C 20090812; CN 1497400 A 20040519; DE 60210973 D1 20060601; DE 60210973 T2 20070104; EP 1406132 A1 20040407; EP 1406132 B1 20060426; HK 1063221 A1 20041217; JP 2004125797 A 20040422; JP 4343642 B2 20091014; KR 100972914 B1 20100728; KR 20040031598 A 20040413; SG 107155 A1 20041129; TW 200405959 A 20040416; TW I269949 B 20070101

DOCDB simple family (application)  
**US 67815703 A 20031006**; AT 02079166 T 20021004; CN 200310100749 A 20031008; DE 60210973 T 20021004; EP 02079166 A 20021004; HK 04106002 A 20040810; JP 2003345467 A 20031003; KR 20030068112 A 20031001; SG 200305760 A 20031002; TW 92126886 A 20030929