

Title (en)
GASKET TOOL FOR HOSE COUPLINGS

Title (de)
WERKZEUG FÜR DICHTUNGEN EINER SCHLAUCHKUPPLUNG

Title (fr)
OUTIL DE JOINT POUR RACCORDS DE TUYAUTERIE

Publication
EP 1409204 A2 20040421 (EN)

Application
EP 02750091 A 20020717

Priority
• US 0222644 W 20020717
• US 30730001 P 20010723

Abstract (en)
[origin: WO03009970A2] A tool for inserting and removing gaskets from hose couplings includes a shaft having a nose and heel attached at one end of the shaft. The heel includes a flat, bottom surface that is pressed against the gasket in order to push the gasket into place. The heel may have a sufficiently large surface area to not cause undue markings or damage to the gasket when it is inserted. When the gasket is to be removed, the nose is inserted between an underside of the gasket and the gasket seat. The heel is then moved into contact with the gasket seat and used as a fulcrum by which the nose is lifted away from the gasket seat. This lifting movement causes the gasket to be lifted out of the hose coupling.

IPC 1-7
B25B 27/00

IPC 8 full level
F16J 15/00 (2006.01); **B25B 27/00** (2006.01)

CPC (source: EP US)
B25B 27/0028 (2013.01 - EP US)

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR

DOCDB simple family (publication)
WO 03009970 A2 20030206; WO 03009970 A3 20030530; AU 2002320567 A1 20030217; BR 0211278 A 20061031; CA 2454798 A1 20030206; EP 1409204 A2 20040421; JP 2005526931 A 20050908; MX PA04000718 A 20040420; US 2003029277 A1 20030213

DOCDB simple family (application)
US 0222644 W 20020717; AU 2002320567 A 20020717; BR 0211278 A 20020717; CA 2454798 A 20020717; EP 02750091 A 20020717; JP 2003515349 A 20020717; MX PA04000718 A 20020717; US 19718302 A 20020717