

Title (en)
CONNECTING DEVICE FOR THERMAL INSULATING CONNECTION BETWEEN AT LEAST TWO WALLS OF A BUILDING, AND METHOD FOR MAKING SAME

Title (de)
VORRICHTUNG ZUM THERMISCH ISOLIERTEN VERBINDEN WENIGSTENS ZWEIER BAUWÄNDE UND HERSTELLUNGSVERFAHREN EINER SOLCHEN VORRICHTUNG

Title (fr)
DISPOSITIF DE LIAISON REALISANT, DE MANIERE ISOLEE THERMIQUEMENT, LA LIAISON ENTRE AU MOINS DEUX PAROIS D'UNE CONSTRUCTION, ET PROCEDE DE REALISATION D'UN TEL DISPOSITIF

Publication
EP 1409813 A2 20040421 (FR)

Application
EP 02790204 A 20020719

Priority
• FR 0202588 W 20020719
• FR 0109797 A 20010723

Abstract (en)
[origin: FR2827620A1] The connection has an insulating element (30), comprising a core (31) and flange(s) (32,33) in a U-shaped configuration, situated on the end of a second partition inside the first. The concave side of the insulating element faces the second partition. The distance between the flanges is at least equivalent to the thickness of the second partition.

IPC 1-7
E04G 21/12

IPC 8 full level
E04B 1/76 (2006.01); **E04B 1/00** (2006.01); **E04B 5/32** (2006.01); **E04G 21/12** (2006.01)

CPC (source: EP)
E04B 1/0038 (2013.01); **E04B 5/32** (2013.01); **E04G 21/125** (2013.01); **E04B 2001/7679** (2013.01)

Citation (search report)
See references of WO 03010394A2

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR

DOCDB simple family (publication)
FR 2827620 A1 20030124; FR 2827620 B1 20040702; AT E542004 T1 20120215; AU 2002334017 A1 20030217; EP 1409813 A2 20040421; EP 1409813 B1 20120118; PL 367095 A1 20050221; RU 2004105157 A 20050620; WO 03010394 A2 20030206; WO 03010394 A3 20040122

DOCDB simple family (application)
FR 0109797 A 20010723; AT 02790204 T 20020719; AU 2002334017 A 20020719; EP 02790204 A 20020719; FR 0202588 W 20020719; PL 36709502 A 20020719; RU 2004105157 A 20020719