

Title (en)

METHOD AND DEVICE FOR THE CORRECTION OF THE DYNAMIC ERROR OF A SENSOR

Title (de)

VERFAHREN UND VORRICHTUNG ZUR KORREKTUR DES DYNAMIKFEHLERS EINES SENSORS

Title (fr)

PROCEDE ET DISPOSITIF DE CORRECTION DE L'ERREUR DYNAMIQUE D'UN DETECTEUR

Publication

**EP 1409965 A1 20040421 (DE)**

Application

**EP 02776655 A 20020705**

Priority

- DE 0202465 W 20020705
- DE 10133524 A 20010711

Abstract (en)

[origin: WO03010497A1] A method and device for the correction of the dynamic error of a sensor are disclosed. The sensor output signal is fed to a filter circuit and a correction circuit to carry out said correction. The correction circuit is supplied with one or several filtered signals from the filter circuit and generates a corrected sensor signal from information derived thereby from a comparison of the filtered signal with the unfiltered sensor output signal, or a corrected signal derived therefrom, which is supplied to a further processing.

IPC 1-7

**G01F 1/696; G01F 1/72; G01F 15/04; F02D 41/18**

IPC 8 full level

**G01F 1/00** (2006.01); **F02D 41/18** (2006.01); **G01F 1/68** (2006.01); **G01F 1/696** (2006.01); **G01F 1/72** (2006.01); **G01F 15/04** (2006.01);  
**H03K 17/94** (2006.01)

CPC (source: EP US)

**F02D 41/18** (2013.01 - EP US); **G01F 1/696** (2013.01 - EP US); **G01F 1/72** (2013.01 - EP US); **G01F 15/043** (2013.01 - EP US);  
**F02D 2041/1432** (2013.01 - EP US)

Citation (search report)

See references of WO 03010497A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR

DOCDB simple family (publication)

**WO 03010497 A1 20030206**; DE 10133524 A1 20030130; EP 1409965 A1 20040421; JP 2004536320 A 20041202;  
US 2004153780 A1 20040805

DOCDB simple family (application)

**DE 0202465 W 20020705**; DE 10133524 A 20010711; EP 02776655 A 20020705; JP 2003515824 A 20020705; US 48156103 A 20031219