

Title (en)

METHOD AND DEVICE FOR IDENTIFYING DOUBLE FEEDS

Title (de)

VERFAHREN UND ANORDNUNG ZUM ERKENNEN VON DOPPELABZÜGEN

Title (fr)

PROCEDE ET DISPOSITIF DE DETECTION D'UN ENLEVEMENT EN DOUBLE

Publication

EP 1421022 B1 20050126 (DE)

Application

EP 02772021 A 20020813

Priority

- DE 0202961 W 20020813
- DE 10142331 A 20010830

Abstract (en)

[origin: WO03018449A1] The invention relates to a method and a device for identifying overlap during the successive transport of flat mail in a double belt system. After edges have been detected on both sides of the transport path and after the distances between the detected edges and the respective guiding front edge measured by a light barrier have been determined, both sides of the longitudinal sides of the mail are acted upon with different transport speeds, ensuring that the minimum gaps are maintained. The distances between the edges and the guiding front edge are then re-measured. A double feed is detected if there is a change in distance.

IPC 1-7

B65H 7/12; **B65H 29/12**

IPC 8 full level

B65H 7/12 (2006.01); **B65H 29/12** (2006.01)

CPC (source: EP US)

B65H 7/125 (2013.01 - EP US); **B65H 29/12** (2013.01 - EP US); **B65H 2301/44316** (2013.01 - EP US); **B65H 2301/44514** (2013.01 - EP US); **B65H 2301/4474** (2013.01 - EP US); **B65H 2404/2691** (2013.01 - EP US); **B65H 2511/514** (2013.01 - EP US); **B65H 2513/10** (2013.01 - EP US); **B65H 2553/412** (2013.01 - EP US); **B65H 2553/414** (2013.01 - EP US); **B65H 2701/131** (2013.01 - EP US); **B65H 2701/1916** (2013.01 - EP US)

Designated contracting state (EPC)

BE DE FR GB IT

DOCDB simple family (publication)

WO 03018449 A1 20030306; DE 10142331 C1 20030327; DE 50202136 D1 20050303; EP 1421022 A1 20040526; EP 1421022 B1 20050126; US 2004195760 A1 20041007

DOCDB simple family (application)

DE 0202961 W 20020813; DE 10142331 A 20010830; DE 50202136 T 20020813; EP 02772021 A 20020813; US 48833004 A 20040227