

Title (en)
LASHING ROD

Title (de)
FESTBINDSTANGE

Title (fr)
TIGE D'AMARRAGE

Publication
EP 1424277 B1 20100505 (EN)

Application
EP 02760807 A 20020904

Priority
• JP 0209002 W 20020904
• JP 2001267118 A 20010904

Abstract (en)

[origin: EP1424277A1] In a lashing rod in which a hook member can be reliably held in an engaged state relative to two kinds of corner fittings of which the engaging holes have different width dimensions, a coupling ring 2 elongated in the longitudinal direction of a rod 1 is provided on the tip of the rod 1, and a coupling plate portion 13 provided on the hook member 11 is inserted in the coupling ring 2 so as not to come out. A engaging head 12 engageable in engaging holes H1, H2 formed in corner fittings C-2 of a container B is provided on the hook member 11. A protrusion 14 is formed on the rear end of the front surface of an engaging plate portion 12a of the engaging head 12 so that the engaging head 12 can be kept in an engaged state relative to the two kinds of engaging holes H1, H2 having different width dimensions. <IMAGE>

IPC 8 full level
B63B 25/00 (2006.01); **B65D 90/00** (2006.01)

CPC (source: EP KR)
B63B 25/00 (2013.01 - KR); **B65D 90/0006** (2013.01 - EP); **B65D 2590/0016** (2013.01 - EP)

Cited by
DE102011055287A1; WO2014169903A3

Designated contracting state (EPC)
DE ES NL SE

DOCDB simple family (publication)

EP 1424277 A1 20040602; **EP 1424277 A4 20070404**; **EP 1424277 B1 20100505**; CN 1305742 C 20070321; CN 1633378 A 20050629;
DE 60236298 D1 20100617; JP 2003072673 A 20030312; JP 3643804 B2 20050427; KR 100917032 B1 20090910;
KR 20040029018 A 20040403; WO 03020580 A1 20030313

DOCDB simple family (application)

EP 02760807 A 20020904; CN 02816203 A 20020904; DE 60236298 T 20020904; JP 0209002 W 20020904; JP 2001267118 A 20010904;
KR 20047002703 A 20020904