

Title (en)  
Construction formwork

Title (de)  
Baugerüst

Title (fr)  
Echafaudage de construction

Publication  
**EP 1426524 A2 20040609 (DE)**

Application  
**EP 03026948 A 20031125**

Priority  
DE 10256609 A 20021203

Abstract (en)  
The scaffold consists of uprights to which are connected railing struts (1), each of which has an elongated hole (2) on one or both ends for the hanging on the scaffold. The slot length of the elongated hole corresponds at least to the difference between the scaffold section length and the length of the diagonal of the scaffold section. The slot length or overall slot length is equal to or more than 10cm. The slot length per each section size of the scaffold lies within the range of 40cm to 60cm. An Independent claim is included for railing struts for a scaffold.

Abstract (de)  
Bei einem Baugerüst aus Gerüststäben und damit verbindbaren Geländerstreben, sind diese an einem oder beiden Enden mit einem Langloch versehen, dessen Länge mindestens die Differenz zwischen der Feldlänge des Gerüsts und der Diagonalen dieses Gerüstfeldes entspricht.  
<IMAGE>

IPC 1-7  
**E04G 1/26**

IPC 8 full level  
**E04G 5/14** (2006.01)

CPC (source: EP)  
**E04G 5/14** (2013.01); **E04G 5/142** (2013.01); **E04G 5/147** (2013.01)

Cited by  
EP3012385A1; EP3839172A1

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)  
**EP 1426524 A2 20040609; EP 1426524 A3 20041020; DE 10256609 A1 20040617**

DOCDB simple family (application)  
**EP 03026948 A 20031125; DE 10256609 A 20021203**