

Title (en)
Construction formwork

Title (de)
Baugerüst

Title (fr)
Echafaudage de construction

Publication
EP 1426524 A3 20041020 (DE)

Application
EP 03026948 A 20031125

Priority
DE 10256609 A 20021203

Abstract (en)
[origin: EP1426524A2] The scaffold consists of uprights to which are connected railing struts (1), each of which has an elongated hole (2) on one or both ends for the hanging on the scaffold. The slot length of the elongated hole corresponds at least to the difference between the scaffold section length and the length of the diagonal of the scaffold section. The slot length or overall slot length is equal to or more than 10cm. The slot length per each section size of the scaffold lies within the range of 40cm to 60cm. An Independent claim is included for railing struts for a scaffold.

IPC 1-7
E04G 1/26

IPC 8 full level
E04G 5/14 (2006.01)

CPC (source: EP)
E04G 5/14 (2013.01); **E04G 5/142** (2013.01); **E04G 5/147** (2013.01)

Citation (search report)

- [XY] DE 19712071 A1 19980115 - NITSCHKE WERNER [DE]
- [Y] DE 29913858 U1 19991202 - THYSEN HUENNEBECK GMBH [DE]
- [Y] US 6279880 B1 20010828 - HAWKS JR WILLIAM ROBERT [US]
- [X] CA 2385380 A1 20021130 - ONO TATSUO [JP]

Cited by
EP3012385A1; EP3839172A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 1426524 A2 20040609; EP 1426524 A3 20041020; DE 10256609 A1 20040617

DOCDB simple family (application)
EP 03026948 A 20031125; DE 10256609 A 20021203