

Title (en)  
OUTPUT MANAGEMENT SYSTEM AND METHOD FOR ENABLING PRINTING VIA WIRELESS DEVICES

Title (de)  
AUSGANGSMANAGEMENTSYSTEM UND VERFAHREN ZUM ERMÖGLICHEN DES DRUCKENS ÜBER DRAHTLOSE EINRICHTUNGEN

Title (fr)  
SYSTEME ET PROCÉDE DE GESTION DE SORTIE PERMETTANT L'IMPRESSION VIA DES DISPOSITIFS SANS FIL

Publication  
**EP 1428134 A2 20040616 (EN)**

Application  
**EP 02773235 A 20020822**

Priority

- US 0226783 W 20020822
- US 31441201 P 20010822
- US 35175402 P 20020123
- US 9883202 A 20020313
- US 10452802 A 20020321
- US 22558102 A 20020821

Abstract (en)  
[origin: WO03019403A2] A system and method for managing output such as printing, faxing, and e-mail over various types of computer networks. In one aspect, the method provides for printing via a wireless device. The system provides rendereable data to the wireless device by which a user-interface (UI) (76) may be rendered. The UI enables users (u1) to select source data and an output device on which the source data are to be printed. The source data are then retrieved from a local or remote store (74) and forward to a print service, which renders output image data corresponding to the source data and the output device that was selected. The output image data are then submitted to the output device to be physically rendered. The user-interfaces enable wire and wireless devices to access the system. The system enables documents (72) to be printed by reference, and enables access to resources behind firewalls.

[origin: WO03019403A2] A system and method for managing output such as printing, faxing, and e-mail over various types of computer networks. In one aspect, the method provides for printing via a wireless device. The system provides rendereable data to the wireless device by which a user-interface UI 76 may be rendered. The UI enables users u1 to select source data and an output device on which the source data are to be printed. The source data are then retrieved from a local or remote store 74 and forward to a print service, which renders output image data corresponding to the source data and the output device that was selected. The output image data are then submitted to the output device to be physically rendered. The user-interfaces enable wire and wireless devices to access the system. The system enables documents 72 to be printed by reference, and enables access to resources behind firewalls.

IPC 1-7  
**G06F 15/16**

IPC 8 full level  
**B41J 29/38** (2006.01); **G06F 3/12** (2006.01); **H04L 12/28** (2006.01); **H04L 12/56** (2006.01); **H04L 29/06** (2006.01); **H04L 29/08** (2006.01)

CPC (source: EP KR US)  
**G06F 3/12** (2013.01 - KR); **H04L 67/02** (2013.01 - EP); **H04L 67/04** (2013.01 - EP); **H04L 67/288** (2013.01 - EP); **H04L 67/56** (2022.05 - EP); **H04L 67/59** (2022.05 - EP US); **H04N 1/00416** (2013.01 - EP); **H04N 1/32767** (2013.01 - EP); **H04L 63/0272** (2013.01 - EP); **H04L 63/0281** (2013.01 - EP); **H04L 63/029** (2013.01 - EP); **H04L 63/08** (2013.01 - EP); **H04L 67/568** (2022.05 - EP); **H04W 12/06** (2013.01 - EP US)

Citation (search report)  
See references of WO 03019403A2

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR

DOCDB simple family (publication)  
**WO 03019403 A2 20030306**; **WO 03019403 A3 20031120**; CN 1575460 A 20050202; EP 1428134 A2 20040616; JP 2005501341 A 20050113; KR 20040029438 A 20040406

DOCDB simple family (application)  
**US 0226783 W 20020822**; CN 02820979 A 20020822; EP 02773235 A 20020822; JP 2003523393 A 20020822; KR 20047002681 A 20020822