

Title (en)

Pressure fluid cylinder particularly for a drafting arrangement in a textile machines

Title (de)

Druckmittelzylinder, insbesondere für ein Streckwerk einer Textilmaschine

Title (fr)

Vérin à pression fluide, particulièrement pour un arrangement d'etirage dans une machine textile

Publication

**EP 1428914 B1 20070829 (DE)**

Application

**EP 03104432 A 20031127**

Priority

DE 10255640 A 20021128

Abstract (en)

[origin: EP1428914A2] A switching disc (12) intervenes between piston (2) and cylinder base (6) on the pressure chamber (8) side. An initial compressed air pulse into the pressure chamber, overcomes friction and as a result, the disc reaches a position near the piston. The outer diameter of the disc is less than the inner diameter of the casing, but presents a maximal working area for the pressure pulse. The disc is fitted to a coaxial extension (10) of the piston rod (3) which projects into the pressure chamber (8). The disc includes an inner radial extension bush (10), shaped for guidance along the rod. The disc grips the piston rod by means of an elastomer ring (15), exerting friction. The ring is held in a corresponding groove in the inner edge of the disc. The casing (1) has an internal stop ring (16) formation. This is an end stop for the piston on one side, and an end stop for the disc located close to the piston, on the other side. The pneumatic cylinder action is single-stroke. The disc is located in the sole pressure chamber which lies on the opposite side of the piston from the piston rod opening. The piston rod leaves the pot-shaped cylinder at a basal opening. At the other end, the cylinder has a separate base (6) which closes it. The base has a connection (7) for the pressure medium. This is applied to the pressure chamber and a guide recess (9) corresponding with the piston rod extension.

IPC 8 full level

**D01H 5/52** (2006.01); **F16J 10/02** (2006.01); **F15B 15/28** (2006.01); **F15B 19/00** (2006.01)

CPC (source: EP US)

**F15B 15/2807** (2013.01 - EP US); **F15B 15/2892** (2013.01 - EP US); **F15B 19/005** (2013.01 - EP US)

Cited by

DE102012007777A1; US7610660B2; CN102691145A; DE102006048742B4; DE102021120188A1; DE102021120662A1; US7603750B2; WO2024132128A1

Designated contracting state (EPC)

CH DE FR GB IT LI

DOCDB simple family (publication)

**DE 10255640 B3 20040122**; CN 1316168 C 20070516; CN 1521408 A 20040818; DE 50308057 D1 20071011; EP 1428914 A2 20040616; EP 1428914 A3 20050330; EP 1428914 B1 20070829; JP 2004176248 A 20040624; JP 4391807 B2 20091224; US 2004139851 A1 20040722; US 7174606 B2 20070213

DOCDB simple family (application)

**DE 10255640 A 20021128**; CN 200310118704 A 20031128; DE 50308057 T 20031127; EP 03104432 A 20031127; JP 2003399876 A 20031128; US 72174103 A 20031126