

Title (en)
ABSORBENT STRUCTURE ABSORBENT ARTICLE WATER ABSORBENT RESIN AND ITS PRODUCTION PROCESS AND EVALUATION METHOD

Title (de)
ABSORBIERENDE STRUKTUR UND GEGENSTAND, WASSER ABSORBIERENDES HARZ, VERFAHREN ZU SEINER HERSTELLUNG UND AUSWERTUNGSVERFAHREN

Title (fr)
STRUCTURE ABSORBANTE, ARTICLE ABSORBANT, RESINE ABSORBANT L'EAU ET SA PRODUCTION

Publication
EP 1429703 A2 20040623 (EN)

Application
EP 02799478 A 20020918

Priority
• JP 0209567 W 20020918
• JP 2001285752 A 20010919
• JP 2001375375 A 20011210
• JP 2002072476 A 20020315
• JP 2002106565 A 20020409

Abstract (en)
[origin: WO03026707A2] The present invention provides: an absorbent structure and an absorbent article, which are excellent in both liquid diffusion ability and liquid storage ability, and which are excellent in the dry feeling and the amount of wet back of the aqueous liquid, and which can realize the thinning and lightening more and a water-absorbent resin fitly usable for the above absorbent structure and absorbent article. The absorbent structure, according to the present invention, comprises a liquid-diffusing member and a water-absorbent resin, with the absorbent structure being characterized in that when the capillary absorption index of the liquid-diffusing member at a height of 40 cm is referred to as A $A \geq 0.10$, the capillary absorption index B of the water-absorbent resin at a height of 40 cm satisfies the following equation: $B/A \geq 0.7$ equation 1.
[origin: WO03026707A2] The present invention provides: an absorbent structure and an absorbent article, which are excellent in both liquid diffusion ability and liquid storage ability, and which are excellent in the dry feeling and the amount of wet back of the aqueous liquid, and which can realize the thinning and lightening more; and a water-absorbent resin fitly usable for the above absorbent structure and absorbent article. The absorbent structure, according to the present invention, comprises a liquid-diffusing member and a water-absorbent resin, with the absorbent structure being characterized in that when the capillary absorption index of the liquid-diffusing member at a height of 40 cm is referred to as A ($A \geq 0.10$), the capillary absorption index B of the water-absorbent resin at a height of 40 cm satisfies the following equation: $B/A \geq 0.7$ (equation 1).

IPC 1-7
A61F 13/15

IPC 8 full level
C08L 101/14 (2006.01); **A61F 13/15** (2006.01); **A61L 15/60** (2006.01); **C08J 3/12** (2006.01); **G01N 5/02** (2006.01)

CPC (source: EP)
A61F 13/15203 (2013.01); **A61F 13/53** (2013.01); **A61F 13/5376** (2013.01); **A61L 15/60** (2013.01); **C08J 3/12** (2013.01); **C08L 101/14** (2013.01); **A61F 2013/15463** (2013.01); **A61F 2013/15487** (2013.01); **A61F 2013/1552** (2013.01); **C08J 2300/14** (2013.01); **C08J 2333/06** (2013.01); **G01N 5/025** (2013.01)

Citation (search report)
See references of WO 03026707A2

Cited by
WO2017170501A1; US11602577B2

Designated contracting state (EPC)
BE DE GB IT

DOCDB simple family (publication)
WO 03026707 A2 20030403; **WO 03026707 A3 20031030**; EP 1429703 A2 20040623; PL 365287 A1 20041227

DOCDB simple family (application)
JP 0209567 W 20020918; EP 02799478 A 20020918; PL 36528702 A 20020918