

Title (en)  
Pivoted barrier

Title (de)  
Schwenkbare Sperre

Title (fr)  
Barrière pivotante

Publication  
**EP 1445382 B1 20080813 (FR)**

Application  
**EP 04356003 A 20040112**

Priority  
FR 0301247 A 20030204

Abstract (en)  
[origin: EP1445382A1] The barrier has a locking mechanism with turntable including three holes (53), where two holes are separated by 90 degrees and third hole is separated by 180 degrees with respect to one of the two holes. A plate (43) is engaged between a turntable and a plate (41) to cover one of the holes (53) for forming a shallow hole to immobilize an arm in an opening position. The other holes (53, 63) form a deep hole for locking the arm. The plate (41) is mounted on the turntable in two different positions and includes three holes (63). Two plate holes that are separated by 90 degrees coincide with corresponding holes of the turntable in one position. Third and first holes of the plate separated by 180 degrees coincide with corresponding holes of the turntable. A striking part (42) is mounted on the plate (41) in two different positions.

IPC 8 full level  
**E01F 13/06** (2006.01); **E06B 11/08** (2006.01)

CPC (source: EP)  
**E01F 13/06** (2013.01); **E06B 11/085** (2013.01)

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)  
**EP 1445382 A1 20040811; EP 1445382 B1 20080813**; AT E404735 T1 20080815; DE 602004015651 D1 20080925; ES 2312943 T3 20090301; FR 2850682 A1 20040806; FR 2850682 B1 20050408

DOCDB simple family (application)  
**EP 04356003 A 20040112**; AT 04356003 T 20040112; DE 602004015651 T 20040112; ES 04356003 T 20040112; FR 0301247 A 20030204