

Title (en)
METHOD AND DEVICE FOR THE DRYING AND/OR CROSS-LINKING OF A COATING ON A METAL STRIP WHICH CONTAINS SOLVENTS

Title (de)
VERFAHREN UND VORRICHTUNG ZUM TROCKNEN UND/ODER VERNETZEN EINER LÖSEMittelHALTIGEN BESCHICHTUNG EINES METALLBANDS

Title (fr)
PROCEDE ET DISPOSITIF DE SECHAGE ET/OU RETICULATION D'UN REVETEMENT D'UNE BANDE METALLIQUE CONTENANT UN SOLVANT

Publication
EP 1446236 A2 20040818 (DE)

Application
EP 02781203 A 20021002

Priority
• DE 10158008 A 20011122
• EP 0211031 W 20021002

Abstract (en)
[origin: WO03043746A2] A method and a device for the drying and/or cross-linking of a coating on a metal strip (8) which contains solvents are disclosed, whereby the coated metal strip is fed through a drying device in a conventional manner. Within the above said strip is treated with infra-red radiation, in particular in the wavelength range between about 0.8microm and about 1.5microm. A gas is simultaneously supplied to the interior of the drying device, the temperature of which is above the condensation temperature of the solvent. In comparison to conventional methods and devices of the above type which operate with induction coils, it is primarily the coating and not the base material, in other words the metal strip (8), which is heated. The above leads to more rapid drying and cross-linking times and an improved thermal efficiency.

IPC 1-7
B05D 3/02

IPC 8 full level
B05D 3/02 (2006.01); **B05D 7/14** (2006.01); **F26B 3/28** (2006.01); **F26B 13/10** (2006.01)

CPC (source: EP)
B05D 3/0263 (2013.01); **B05D 7/14** (2013.01); **F26B 3/283** (2013.01); **F26B 13/10** (2013.01)

Citation (search report)
See references of WO 03043746A2

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR

DOCDB simple family (publication)
WO 03043746 A2 20030530; WO 03043746 A3 20040304; WO 03043746 A8 20040521; DE 10158008 A1 20030605; EP 1446236 A2 20040818

DOCDB simple family (application)
EP 0211031 W 20021002; DE 10158008 A 20011122; EP 02781203 A 20021002