

Title (en)

Locking system, in particular for a door, a window, or similar

Title (de)

Schliessanlage, insbesondere Türverschluss, Fensterverschluss oder dergleichen

Title (fr)

Système de verrouillage, notamment pour une porte, une fenêtre, ou similaire

Publication

**EP 1452675 B1 20090325 (DE)**

Application

**EP 03026984 A 20031126**

Priority

DE 10308243 A 20030225

Abstract (en)

[origin: EP1452675A2] A locking system for a door or window has a main lock operated by a handle and/or key and a secondary lock operated by a slider (5) coupled to a rack and pinion servo drive. The connection between the rack and the slider is via a pin and slot which, when the servo drive is set into the parking position, provides sufficient movement in the coupling to cater for manual operation of the lock, i.e. the lock can be operated manually without dragging the servo drive. The maximum play in the coupling exceeds the manual displacement by 2 mm in either direction. The invention is also applicable to locking systems with a servo drive for both the main and secondary catches.

IPC 8 full level

**E05C 9/00** (2006.01); **E05B 47/00** (2006.01); **E05C 9/02** (2006.01); **E05C 9/18** (2006.01)

CPC (source: EP)

**E05C 9/023** (2013.01); **E05B 47/0012** (2013.01); **E05B 2047/0016** (2013.01); **E05B 2047/002** (2013.01); **E05C 9/1875** (2013.01)

Cited by

US11162279B1; GB2402424B; DE102008014548A1; EP2101020A3; DE102008014548B4; EP2626491A3

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)

**EP 1452675 A2 20040901**; **EP 1452675 A3 20070509**; **EP 1452675 B1 20090325**; AT E426722 T1 20090415; DE 10308243 A1 20040916; DE 10308243 B4 20061102; DE 50311333 D1 20090507

DOCDB simple family (application)

**EP 03026984 A 20031126**; AT 03026984 T 20031126; DE 10308243 A 20030225; DE 50311333 T 20031126