

Title (en)
PERCUSSION OR HAMMER DRILL

Title (de)
SCHLAG- ODER HAMMERBOHRER

Title (fr)
OUTIL DE PERCAGE PAR PERCUSSION OU PAR MARTELAGE

Publication
EP 1455978 B1 20051019 (DE)

Application
EP 02793032 A 20021216

Priority

- EP 0214329 W 20021216
- LU 90862 A 20011217

Abstract (en)
[origin: WO03051565A1] A percussion or hammer drill comprises a drill plate (18, 18'), arranged in the head end (16) of a drill shaft (14), extending completely across the diameter of the drill shaft (14) and comprising an open front face (32). Wedge-shaped cutting edges and flanks (34, 34', 36, 36') form two main cutters (38, 38') on said front face (32), whereby a plane running through the drill axis (21) forms a mid-plane (40) of both main cutters (38, 38'). The main cutters (38, 38') form a tip angle (46) in the range of 140 DEG to 180 DEG and are separated by a central point (48, 48').

IPC 1-7
B23B 51/00

IPC 8 full level
B23B 51/00 (2006.01); **B23B 51/02** (2006.01); **B28D 1/14** (2006.01)

CPC (source: EP US)
B23B 51/02 (2013.01 - EP US); **B23B 2226/75** (2013.01 - EP US); **B23B 2251/14** (2013.01 - EP US); **B23B 2251/50** (2022.01 - EP US);
Y10T 408/9097 (2015.01 - EP US)

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SI SK TR

DOCDB simple family (publication)
WO 03051565 A1 20030626; AT E307001 T1 20051115; AU 2002358725 A1 20030630; CN 1313235 C 20070502; CN 1604829 A 20050406;
DE 50204634 D1 20051124; DK 1455978 T3 20060227; EP 1455978 A1 20040915; EP 1455978 B1 20051019; ES 2249629 T3 20060401;
JP 2005511336 A 20050428; JP 3954029 B2 20070808; LU 90862 B1 20030618; US 2005103532 A1 20050519; US 7314102 B2 20080101

DOCDB simple family (application)
EP 0214329 W 20021216; AT 02793032 T 20021216; AU 2002358725 A 20021216; CN 02825202 A 20021216; DE 50204634 T 20021216;
DK 02793032 T 20021216; EP 02793032 A 20021216; ES 02793032 T 20021216; JP 2003552480 A 20021216; LU 90862 A 20011217;
US 49840804 A 20041223